

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

C/SF
SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation /

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660 FNL & FEL, Sec. 10-6S-25E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Surface Casing; Production Casing

SUBSEQUENT REPORT OF

☒

☐

☐


☐

☐

☐

☐

☐



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 12-1/4" hole 7:30 AM 4-10-82. Ran 22 joints of 8-5/8" J-55 24# casing set 882'. 1-Texas Pattern guide shoe set 882'. Flapper float set 842'. Cemented w/500 sacks Halliburton Lite and 2% CaCl. Tailed in w/200 Class C 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. Cement circulated 50 sacks. PD 4:30 AM 4-12-82. Bumped plug to 750 psi, released pressure and float held okay. WOC. Drilled out 10:30 PM 4-12-82. WOC 18 hours. Nipped up and tested to 1000 psi okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling. TD 4250'. Ran 105 joints 4-1/2" 9.5# J-55 casing set 4250'. 1-Halliburton guide shoe set 4232'. Diff-fill float collar set 4193'. Used 250 gallons mud flush ahead of 350 sacks 50/50 Poz "C" with 2% gel, .3% Halad-4, .3% CFR-2. PD 3:00 PM 4-18-82. Bumped plug to 750 psi, released pressure and float held okay. WOC.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Engineering Secty DATE MAY 27 1982

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____

CONDITIONS OF APPROVAL, IF ANY:

