

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY  
RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a new reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐  
2. NAME OF OPERATOR  
Yates Petroleum Corporation  
3. ADDRESS OF OPERATOR  
207 South 4th St., Artesia, NM 88210  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660 FNL & FEL, Sec. 10-6S-25E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

O. C. D.  
ARTESIA, OFFICE

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

(other) Perforate, Treat

- ☐  
☒  
☒  
☐  
☐  
☐  
☐  
☐

5. LEASE  
NM 14755  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Powers OL Federal  
9. WELL NO.  
5  
10. FIELD OR WILDCAT NAME  
Pecos Slope Abo  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Unit A, Sec. 10-T6S-R25E  
12. COUNTY OR PARISH  
Chaves  
13. STATE  
NM  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3915.9' GR

RECEIVED  
MAY 21 1982

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 4250'. WIH and perforated 3707-3867' w/25 .50" holes as follows: 3707, 08, 20, 21, 39, 40, 41, 54, 55, 56, 3797, 98, 99, 3800, 01, 02, 03, 3830, 31, 62, 63, 64, 65, 66 & 67'. Acidized perforations 3707-3867' w/5000 gallons 7 1/2% MOD 101 acid and 16 balls. Frac'd perforations 3707-3867' w/60000 gallons gelled KCL wtr, 120000# 20/40 sand. Well cleaned up and stabilized at 610 psi on 1/2" choke = 3900 mcfpd.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED *John A. D. D. D.*

TITLE Engineering Section

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD  
MAY 26 1982  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

RECEIVED  
MAY 21 1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
Set @ ROSWELL, NEW MEXICO