88210

Form Approved Budget Bureau No. 42-R14, 3

## UNITED STATESAL TOSIA, NM

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

NM 28297

6. HE SULTAN ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drift or to de perfor play ballian reservoir. Use Form 9-331-C for such proposals :

gas other

well 🕟 🦠 well 2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17

AT SURFACE: 660' FSL & 1980' FWL, Sec. 26-58-2-1 AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA

SUBSEQUENT REPORT OF:

Z. UMLE AGREEMENT NAME

Everette 00 Federal

9. WHI. NO

16 5. 1170

10. HE DIGRIWH DOAT NAME Pecis Slope Abo

11. SEC. T., R., M., OR BEK, AND SURVEY OF ARLA

nit N. Sec. 26-T5S-R24E

12. COUNTY OR PARISH 13. STATE Chaves NM

14. API NO

15. ELEVATIONS (SHOW DF, KDB, AND WD) 3953.6 GK

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON\*

(otner) Production Casing

U.S. GEOLOGICAL SURVEY

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent week WEShid New MEXITED) dates. including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD 4200'. Ran 104 joints 4-1/2" 9.5# J-55 casing set 4187'. 1-auto fill float shoe set 4187'. Cemented w/35C sacks 50/50 Poz, .6% CF-9. .3% TF-4 and 3% KCL. Compressive strength of cement - 1250 psi in 12 hours. 70 11:15 PM 4-20-82. Bumped plug to 750 psi, released pressure and float held ckay. WCC.

Subsurface Safety Valve: Manu. and Type

Set (a)

Ft

18. Thereby certify that the foregoing is true and correct

SIGNED!

COCC TITLE

Engineering Section:

(This space for Federal or State office use

APPROVED BY CONDITIONS OF APPROVAL IF ANY TITLE

DATE

ACCELLED FOR RECURD

\*See Instructions on Reverse Side