Form 9-331 - NM OIL CONS. COMMI Dec. 1973 Drawer DD	ISSION Form Approved. Budget Bureau No. 42-R1424
DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	0 5. LEASE NM 9982 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or the back to a different reservoir, Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME
 oil gas well other MAY 1 3 1982 NAME OF OPERATOR Yates Petroleum Corporation O. C. D. ADDRESS OF OPERATOR ARTESIA 85900 ADDRESS OF OPERATOR ARTESIA 85900 LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1980 FSL 660 FEL, Sec. 12-6S-25E AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 	 Teckla MD Federal 9. WELL NO. 10. FIELD OR WILDCAT NAME Pecos Slope Abo 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit I, Sec. 12-T6S-R25E 12. COUNTY OR PARISH 13. STATE Chaves NM 14. API NO.
 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3778' GR
TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone on Form 9-330.) & GAS DGICAL SURVEY NEW MEXICO

B.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 14-3/4" hole at 8:00 PM 4-8-82. Set 40' of 20" conductor pipe. Ran 22 joints of 10-3/4" 40.5# casing set at 877'. 1-Texas Pattern notched guide shoe set at 877'. Insert float at 838'. Cemented w/500 sacks Halliburton Lite 2% CaCl2. Tailed in w/200 sacks Class "C" 2% CaCl2. PD 7:15 PM 4-9-82. Bumped plug to 750 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out at 1:15 PM 4-10-82. WOC 18 hours. Nippled up and tested to 1000 psi, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

Subsurface Safety Valve: Man	u. and Type	Set @ Ft.
18. I hereby certify that the fo	oregoing is true and correct	F (0)
SIGNED Luanda	ordlut TITLE Engineering Secty DATE	
1	(This space for Federal or State office use)	ACCEPTED FOR RECORD
APPROVED BY CONDITIONS OF APPROVAL, IF	ANY:	
CONDITIONS OF AFFROMAL, I		MAY 1 2 1982
	*See Instructions on Reverse Side	U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO
	•See Instructions on Reverse Side	ROSWELL, NEW MEXICO