Form 9–331		
Dec. 1973 UNITED	STATES Drawer DO	Form Approved. Budget Bureau No. 42–R1424 5. LEASE
DEPARTMENT OF GEOLOGICA	STATES Drawer in the internet of the internet	NM 28162 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND	REPORTS ONE CELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill reservoir. Use Form 9-331-C for such propo	l or to deepen or plug back to a drifer osals.) MAY o o o	8. FARM OR LEASE NAME
1. oil gas well other		Thorpe <u>MI</u> Federal 9. WELL NO. 7
2. NAME OF OPERATOR Yates Petroleum Cor 3. ADDRESS OF OPERATOR	O. C. D. porationARTESIA, OFFICE	10. FIELD OR WILDCAT NAME Pecos Slope Abo
207 South 4th St.,	Artesia, NM 88210	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT L below.) AT SURFACE: 1650 FNL 165		Unit G, Sec. 3-T7S-R25E 12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:		Chaves NM 14. API NO.
16. CHECK APPROPRIATE BOX TO REPORT, OR OTHER DATA	INDICATE NATURE OF NOTIC	ΣΕ,
REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3750.2' GR
TEST WATER SHUT OFF Image: Constraint of the second se		
SHOOT OR ACIDIZE		(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING U MULTIPLE COMPLETE CHANGE ZONES		change on Form 9-330.)
ABANDON* (other) Production Casing,	Perforate	
including estimated date of star measured and true vertical dept	rting any proposed work. If well hs for all markers and zones pert	set 4190'. Auto fill float shoe
4190'. Cemented w/375 sa -2. Compressive strengt ped plug to 1000 psi, re1 6-3884' w/21 .50" holes a 9' (1 holes) and 3881-388 lons MOD 101 acid and 17	th of cement - 1050 ps leased pressure and fl as follows: 3626-3630 34' (6 holes). Acidiz ball sealers. Frac'd 000 gallons gelled KCL	<pre>i in 12 hours. PD 12:30 PM 4-18-82. oat held okay. WIH and perforated ' (8 holes); 3875-3878' (6 holes); ed perforations 3626-3884' w/3000 perforations 3626-3884' w/1000 water and 100000# 20/40 sand.</pre>
4190'. Cemented w/375 sa -2. Compressive strengt ped plug to 1000 psi, rel 6-3884' w/21 .50" holes a 9' (1 holes) and 3881-388 lons MOD 101 acid and 17 lons MOD 101 acid and 600 1 cleaned up and stabiliz	th of cement - 1050 ps leased pressure and fl as follows: 3626-3630 84' (6 holes). Acidiz ball sealers. Frac'd 000 gallons gelled KCL zed at 210 psi on 1/2"	<pre>i in 12 hours. PD 12:30 PM 4-18-82. oat held okay. WIH and perforated ' (8 holes); 3875-3878' (6 holes); ed perforations 3626-3884' w/3000 perforations 3626-3884' w/1000 water and 100000# 20/40 sand. choke = 1397 mcfpd.</pre>
4190'. Cemented w/375 sa -2. Compressive strengt ped plug to 1000 psi, rel 6-3884' w/21 .50" holes a 9' (1 holes) and 3881-388 lons MOD 101 acid and 17 lons MOD 101 acid and 600 1 cleaned up and stabiliz	Type	<pre>i in 12 hours. PD 12:30 PM 4-18-82. oat held okay. WIH and perforated ' (8 holes); 3875-3878' (6 holes); ed perforations 3626-3884' w/3000 perforations 3626-3884' w/1000 water and 100000# 20/40 sand.</pre>
4190'. Cemented w/375 sa -2. Compressive strengt ped plug to 1000 psi, rel 6-3884' w/21 .50" holes a 9' (1 holes) and 3881-388 lons MOD 101 acid and 17 lons MOD 101 acid and 600 1 cleaned up and stabiliz	th of cement - 1050 ps leased pressure and fl as follows: 3626-3630 84' (6 holes). Acidiz ball sealers. Frac'd 000 gallons gelled KCL ted at 210 psi on 1/2" Type	<pre>i in 12 hours. PD 12:30 PM 4-18-82. oat held okay. WIH and perforated ' (8 holes); 3875-3878' (6 holes); ed perforations 3626-3884' w/3000 perforations 3626-3884' w/1000 water and 100000# 20/40 sand. choke = 1397 mcfpd.</pre>
4190'. Cemented w/375 sa -2. Compressive strengt ped plug to 1000 psi, rel 6-3884' w/21 .50" holes a 9' (1 holes) and 3881-388 lons MOD 101 acid and 17 lons MOD 101 acid and 600 1 cleaned up and stabiliz Subsurface Safety Valve: Manu. and 18. I-hereby certify that the foregoing	Type	<pre>i in 12 hours. PD 12:30 PM 4-18-82. oat held okay. WIH and perforated ' (8 holes); 3875-3878' (6 holes); ed perforations 3626-3884' w/3000 perforations 3626-3884' w/1000 water and 100000# 20/40 sand. choke = 1397 mcfpd. Set @Ft.</pre>
4190'. Cemented w/375 sa -2. Compressive strengt ped plug to 1000 psi, rel 6-3884' w/21 .50" holes a 9' (1 holes) and 3881-388 lons MOD 101 acid and 17 lons MOD 101 acid and 600 1 cleaned up and stabiliz Subsurface Safety Valve: Manu. and 18. I-hereby certify that the foregoing SIGNED (16)	Type	<pre>i in 12 hours. PD 12:30 PM 4-18-82. oat held okay. WIH and perforated ' (8 holes); 3875-3878' (6 holes); ed perforations 3626-3884' w/3000 perforations 3626-3884' w/1000 water and 100000# 20/40 sand. choke = 1397 mcfpd. Set @Ft.</pre>

· ---