

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
JACK GRYNBERG AND ASSOCIATES

3. ADDRESS OF OPERATOR
1050 17th Street, Suite 1950, Denver, CO 80265

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1780' FNL & 1980' FWL of Sec. 12,
AT TOP PROD. INTERVAL: T6S-R24E
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) SPUDDING AND LAID CASING		


5. LEASE
USA-NM-11795 RECEIVED
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
N/A MAY - 6 1982
7. UNIT AGREEMENT NAME
N/A
8. FARM OR LEASE NAME
Hobbs Canyon Federal O. C. D. ARTESIA, OFFICE
9. WELL NO.
5
10. FIELD OR WILDCAT NAME
Pecos Slope Abo Gas
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 12, T 6 S - R 24 E
12. COUNTY OR PARISH
Chaves
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
4110.0'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/19/82 Spudded @ 1PM 4/19/82. Dr1g ahead. Dr1d to 445'.

4/22/82 Ran 10 3/4" 40.5# 55-3 csg. Ran 21 Jts. set @898'. Cement with 300 sxs Halliburton lite, 1/4# flo cel, 2% cal. chl., 300 sxs Class "C", 1/4# flo cel, 2% cal chl. Circ back to surface. PT csg to 1000. WOC 18 Hrs.



Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

MORRIS ELLINGER

TITLE EXPLORATION MANAGER

DATE

4/26/82

MAY 5 1982

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO