

C/SF

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or to back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil ☐ gas ☒ other

SEP 29 1982

2. NAME OF OPERATOR

Yates Petroleum Corporation O. C. D.

3. ADDRESS OF OPERATOR

ARTESIA, OFFICE

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980 FSL & FWL, Sec. 27-6S-25E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Production Casing, Perforate, Treat

5. LEASE

NM 14755

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Powers OL Federal

9. WELL NO.

6

10. FIELD OR WILDCAT NAME

Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit K, Sec. 27-T6S-R25E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3770.7' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 4150'. Ran 101 jts of 4-1/2" 10.5# J-55 casing set at 4150'. 1-regular guide shoe at 4150'. Float collar at 4098'. Cemented w/350 sacks 50/50 Poz, .6% CF-9, .3% TF-4, 3% KCL and .2% AF-11. Compressive strength of cement - 1050 psi in 12 hours. PD 4:45 AM 6-2-82. Bumped plug to 1000 psi, released pressure and float held okay. WOC. WIH and perforated 3701-3949' w/16 .50" holes as follows: 3701, 02, 03, 04, 3746, 47, 48, 49, 83, 87, 99, 89, 3937, 47, 48, 49'. Acidized perforations 3701-3949' w/3000 gallons 7 1/2% Spearhead acid. Frac'd (via casing) w/40000 gallons gelled 2% KCL water and 70000# 20/40 sand. Well cleaned up and flowed 200 psi on 1/4" choke = 313 mcfpd.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *[Signature]*

TITLE Engineering Secty

DATE 7-1-82

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

*[Signature]*  
SEP 28 1982

U.S. GEOLOGICAL SURVEY  
ROSWell, NEW MEXICO