

RECEIVED BY  
Form 9-331  
Dec. 1973

SEP 23 1985

O. C. D.  
ARTESIA, OFFICE

NM OIL CONS. COMMISS  
Drawer DD  
Artesia, NM 88210

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR  
Harper Oil Company

3. ADDRESS OF OPERATOR  
904 Hightower Bldg., Oklahoma City, OK 73102

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 2310' FSL & 1880' FWL  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☒  
(other)

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE 0  
NM - 5X806

6. IF INDIAN, ALLOTTEE OR TRIBE-NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
K-M Federal

9. WELL NO.  
1

10. FIELD OR WILDCAT NAME  
Wildcat. *First Plummer (A)*

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 11-5S-27E

12. COUNTY OR PARISH Chaves 13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3393' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

PROPOSED PLUGGING PROCEDURES:

Starting Date: October 14, 1985

- (1) Set CIBP @ 6700' w/35' cement on top.  
(2) Cut off 5 1/2" casing approximately @ 2000'± and set 100' plug across stubb (50' in & out) and tag.  
(3) Set 100' cement plug from 1850'-1750' and tag shoe plug.  
(4) Set 100' cement plug from 440'-340'.  
(5) Set 50' surface plug.

\* additional plug: 100' cmt 4600'-4500'

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *Joe Garmon* TITLE Operations Manager DATE 9-9-85

APPROVED BY PETER W. CHESTER  
CONDITIONS OF APPROVAL, IF ANY:

SEP 20 1985

BUREAU OF LAND MANAGEMENT  
ROSWELL RESOURCE AREA

See Instructions on Reverse Side