

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐ P&A

2. NAME OF OPERATOR

Yates Petroleum Corporation ✓

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980 FNL & 660 FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☒

(other)

5. LEASE

NM 14983

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Monaghan QY Federal

9. WELL NO.

3

10. FIELD OR WILDCAT NAME

Und. Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit H, Sec. 21-T5S-R24E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3983.6' GR

RECEIVED
(If To Report results of multiple completion or zone change on Form 9-330.)

MAR 4

OIL & GAS

MINERALS MGMT. SERVICE

ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to plug and abandon well as follows:

1. Spot cement plug on existing retainer at 2510' up to 2290'.
 2. Spot cement plug across surface casing shoe (925') from 975' up to 875'.
 3. Set 10 sack plug at surface and install regulation abandonment marker.
- Surface restoration to be in accordance with landowner-operator agreement.

Verbal approval for the above plugging procedure given by Mr. George Stewart, Dept. of Interior, Roswell, on 3-2-83.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED APPROVED TITLE Production Supervisor

DATE 3-2-83

(Orig. Sgd.) GEORGE H. STEWART

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL

MAR 22 1983

TITLE

DATE

FOR
JAMES A. GILLHAM
DISTRICT SUPERVISOR