

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

WATER CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

RECEIVED

MAY - 4 1982

O. C. D.

Form C-103  
Revised 10-1-73

SUNDRY NOTICES AND REPORTS ON WELLS

ARTESIA, OFFICE

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - 27 (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐

GAS WELL ☒

OTHER-

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER N 660 FEET FROM THE South LINE AND 1980 FEET FROM  
THE West LINE, SECTION 2 TOWNSHIP 5S RANGE 24E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)

3922.4' GR

14. Indicate type of lease

State ☒ Fee ☐

15. State Oil & Gas Lease No.

LG-563

7. Unit Agreement Name

8. Farm or Lease Name

Smernoff NL State

9. Well No.

4

10. Field and Pool, or Wildcat

Pecos Slope Abo

12. County  
Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

REPAIR REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

WELL OR ALTER CASING ☐

CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☒

CASING TEST AND CEMENT JOB ☒

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 12-1/4" hole at 3:45 PM 4-30-82. Set 40' of 20" conductor pipe. Ran 21 joints of 8-5/8" 24# J-55 casing set at 850'. 1-Texas Pattern guide shoe at 850'. Insert float at 810'. Cemented w/350 sacks Pacesetter Lite "C" 3% CaCl<sub>2</sub>. Tailed in w/250 sacks Class "C" 2% CaCl<sub>2</sub>. Compressive strength of cement - 1250 psi in 12 hours. PD 12:00 noon 5-1-82. Bumped plug to 750 psi, released pressure and float held okay. Cement circulated 50 sacks to pit. WOC. Drilled out 6:00 AM 5-2-82. WOC 18 hours. Nipped up and tested to 1000 psi, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

By Angela L. Rodditt

TITLE Engineering Secretary

DATE 5-4-82

APPROVED BY Mike W. W.

TITLE OIL AND GAS INSPECTOR

DATE MAY 6 1982

CONDITIONS OF APPROVAL, IF ANY: