

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DEEPER WELL. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

RECEIVED

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator
Yates Petroleum Corporation ✓
Address of Operator
207 South 4th St., Artesia, NM 88210

JUN 24 1982

O. C. D.
ARTESIA, OFFICE

Location of Well
UNIT LETTER N 960 FEET FROM THE South LINE AND 1980 FEET FROM
West THE LINE, SECTION 20 TOWNSHIP 8S RANGE 26E N.M.P.M.

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Name

8. Farm or Lease Name
Bestwall ST Com

9. Well No.
1

10. Field and Pool, or equivalent
Pecos Slope Abo

11. Elevation (Show whether DF, RT, GR, etc.)
3724.2' GR

12. County
Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOBS ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 14-3/4" hole 9:00 AM 6-18-82. Set 40' of 20" conductor pipe. Ran 24 joints of 10-3/4" 40.5# K-55 casing set 960'. 1-Texas Pattern guide shoe at 960'. Insert float at 920'. Cemented w/350 sacks Pacesetter Lite. Tailed in w/350 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 1:15 PM 6-19-82. Bumped plug to 500 psi, released pressure and float held okay. Cement circulated 35 sacks to pit. WOC. Drilled out 7:15 AM 6-20-82. WOC 18 hours. Nipped up and tested to 1000 psi, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

14. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Aracata Dossett

TITLE Engineering Secretary

DATE 6-23-82

APPROVED BY Mike Williams

TITLE OIL AND GAS INSPECTOR

DATE JUN 28 1982

CONDITIONS OF APPROVAL, IF ANY: