ENERGY AND MINERALS DEPARTN	AENT		:			
	🗍 🐘 👌 JIL CONSERVA	TION DIVISIC				
DISTRIBUTION	Р. О. ВОХ	2088	:		Form C-103	
BANTAFE	SANTA FE, NEW	MAINLIE & 1983	•		Revised 10-1-78	
rice VV		JHW.14 43001	•	Sa. Indicate Type c		
U.B.G.S.			5		<b>C</b> >	
LAND OFFICE	}	O. C. D.	-	State	Fon X	
OPERATOR		ARTESIA, OFFICE '	-	5, Stole Oil & Gas	Legan No.	
SUNDRY NOTICES AND REPORTS ON WELLS DO NOT USE THIS FORM FOR PROPOSALS TO DELICIN OF PLUG BACK TO A DIFFERENT RESERVOIR.				7. Unit Agreement Hone		
OIL CAB WELL X	otere. Junk & Abandon	well				
Hame of Operator				8. Farm of Lease Nume		
Yates Petroleum Corporation $~ u$				Sacra SA		
Address of Operator				9. Well No.		
207 South 4th St., Artesia, NM 88210				7		
Location of Well				10. Field and Pool, or Wildcat		
UNIT LETTERO 660 FEET FROM THE South LINE AND 1650 FEET FROM				Pecos Slope Abo		
THE East LINE, SEC	TION 22 TOWNSHIP 65	5 RANGE 25E	NMPH,			
	15. Elevation (Show whether I 3799	<i>DF, RT, CR, etc.)</i> GR		12. County Chaves		
». Check	Appropriate Box To Indicate Na	ature of Notice, Repo	rt or Oth	er Data		
	INTENTION TO:	• •		REPORT OF:		
LAFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	$\square$	ALTERIN	G CASING	
EMPORARILY ABANDON		COMMENCE DRILLING OPNS.			D ABANDONMENT	
ULL OR ALTLE CASING	CHANGE PLANS	CASING TEST AND CEMENT JO				
		OTHER Abando	n		X	
OTHER		·····			L& J	
	Or excitone (l'Institute all parties of date	ite and size particular data				

r. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 14-3/4" hole at 11:30 PM 12-27-82. Ran 29 joints of 10-3/4" 40.5# J-55 ST&C casing set at 850'. 1-Type "M" notched guide shoe set at 850'. Insert float set 818'. Cemented w/400 sacks Pacesetter Lite, 1/4#/sack celloseal and 3% CaCl<sub>2</sub>. Tailed in w/200 sacks Class "C" 2% CaCl<sub>2</sub>. Compressive strength of cement - 1250 psi in 12 hours. PD 11:45 AM 1-1-83. Bumped plug with too much pressure and damaged casing. Casing could not be repaired. Filled casing from 835' back to surface with 400 sacks Class "C" 2% CaCl<sub>2</sub>. PD 6:15 PM 1-4-83. JUNKED AND ABANDONED.

TP 9:9

Post FD-22 2-3-34 2-10A

Will Recm out 1-10-83 + Run 133/8-690t will File C-103