

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug a well or to plug a reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☐ P&A JUN 1 1982
2. NAME OF OPERATOR  
Yates Petroleum Corporation ✓ O. C. D.
3. ADDRESS OF OPERATOR  
ARTESIA OFFICE  
207 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980 FNL & 660 FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input checked="" type="checkbox"/>	<input type="checkbox"/>
(other)	<input type="checkbox"/>	<input type="checkbox"/>

5. LEASE  
NM 29314
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Two Jacks TM Federal
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
Pecos Slope Abo
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Unit II, Sec. 33-T6S-R24E
12. COUNTY OR PARISH 13. STATE  
Chaves NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
4014' GR

RECEIVED  
MAY 10 1982

(NOTE: Report of multiple completion or zone change on Form 9-330.)

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 3950' Propose to plug and abandon by setting Class "C" cement plugs as follows:  
3300-3410' (Abo top @3358')  
1570-1670' (8-5/8" casing set @1622' and circulated)  
25 sack plug at surface with regulation abandonment marker.

Downhole plugs will consist of a minimum of 35 sacks cement and will be tagged. Surface will be restored in accordance with surface use plan. Verbal approval of plugging program given by Mr. James Gillham, USGS, Roswell on May 17, 1982.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED James A. Gillham TITLE Engineering Secty DATE May 26 1982

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED  
MAY 26 1982  
JAMES A. GILLHAM  
DISTRICT SUPERVISOR