MM OIL CONS. COM Drawer DD Artesia, NM 8821 UNITED STATES	MISSION Form Approved. Budget Bureau No. 42-R1424
UNITED STATES 8821 DEPARTMENT OF THE INTERIOR	
	NM 28305
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
reservoir. Use Form 9-331-C for such proposals.) RECEIVED	8. FARM OR LEASE NAME
1. oil gais 🖾 other	Binnion TT Federal
	9. WELL NO.
2. NAME OF OPERATOR SEP 3 0 1982	4
Yates Petroleum Corporation	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR O. C. D.	Pecos Slope Abo
207 South 4th St., ArtesiaARTEBIA80240E	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.) AT SURFACE: 660 FSL & FEL, Sec. 23-75-25E	Unit P, Sec. 23-T7S-R25E
AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	Chaves NM
IS CULCK APPROPRIATE DAY TO INDICATE NATION OF NOTION	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
ALI ONT, ON OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3663.3' GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5003.3 GK
FRACTURE TREAT	
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330.)
CHANGE ZONES -	
ABANDON*	<ul> <li>Alter A strategy</li> </ul>
(other)	OLOGICAL SURVEY

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded a 12-1/4" hole 4:30 PM 5-30-82. Ran 21 joints of 8-5/8" J-55 24# casing set at 846'. 1-Texas Pattern guide shoe at 846'. 1-insert float set 806'. Cemented w/300 sacks Pacesetter Lite with 2% CaCl. Tailed in w/300 sacks Class "C" 2% CaCl<sub>2</sub>. Compressive strength of cement - 1250 psi in 12 hours. PD 6:00 PM 5-31-82. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 35 sacks. WOC. Drilled out 12:00 PM 6-1-82. WOC 18 hrs. Nippled up and tested to 1000 psi, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. Thereby certify that the foregoing is true and correct	
SIGNED A: and a Brillell TITLE Engineering Secty DATE	6-3-82
ACCEPTED FOR RECORD (This space for Federal or State office use)	······································
APPROVED BY	······
SEP 2 8 1982	
U.S. GEOLOGICAL SURVEY-see Instructions on Reverse Side	
ROSWELL, NEW MEXICO	<del></del>
	en en la seconda de la seco