orm 9–331 Dec. 1973 UNITED STATES	
	Form Approved. Budget Bureau No. 42–R1424
UNILU JIAILU	5. LEASE
DEPARTMENT OF THE INTERMORTL CONS. CO	MMISSION022584
GEOLOGICAL SURVEY Drawer DD	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	7. UNIT AGREEMENT NAMERECEIVED
SUNDRY NOTICES AND REPORTS ON WELLS	
oo not use this form for proposals to drill or to deepen or plug back to a differen servoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME OV 1 2 1982
1. oil gas 🕅	Sun Federal
i. oli gas 🔀 other	9. WELL NO. O. C. D.
2. NAME OF OPERATOR STEVENS OPERATING CORPORATION	4 10. FJELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	-Undesignated Abo
P. O. Box 2408, Roswell, NM 88201	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.) AT SURFACE: 660 FNL 660 FEL Sec 28 T7S R26E	1. <u>Sec. 28 T-7-S R-26-E</u> 12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same as above	Chaves NM
AT TOTAL DEPTH: Same as above	14. API NO.
6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3753.2 GR
EST WATER SHUT-OFF	
RACTURE TREAT I I I I I I I I I I I I I I I I I I I	
	(NOTE: Report results of multiple completion or zon change on Form 9–330.)
PULL OR ALTER CASING	
MULTIPLE COMPLETE	
ABANDON*	
other) Perf X	
including estimated date of starting any proposed work. If well is	tate all pertinent details, and give pertinent dates, s directionally drilled, give subsurface locations and nent to this work.)*
including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertir Propose to add perfs at 4315, 16, 17, 18, 4 4429.5, 30, 30.5, 32, 32,5, 33 and acidize perforated intervals.	s directionally drilled, give subsurface locations and nent to this work.)*
including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertir Propose to add perfs at 4315, 16, 17, 18, 4 4429.5, 30, 30.5, 32, 32,5, 33 and acidize	s directionally drilled, give subsurface locations and nent to this work.)*
including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertir Propose to add perfs at 4315, 16, 17, 18, 4 4429.5, 30, 30.5, 32, 32,5, 33 and acidize perforated intervals.	addrectionally drilled, give subsurface locations and hent to this work.)* add, 45, 50, 50.5, 52, 52.5, 53, interval and then frac all DIFCERVED HOV 3 1982
including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertir Propose to add perfs at 4315, 16, 17, 18, 4 4429.5, 30, 30.5, 32, 32,5, 33 and acidize	a directionally drilled, give subsurface locations and hent to this work.)* a344, 45, 50, 50.5, 52, 52.5, 53, interval and then frac all DISCENTED LOV 3 1982
<ul> <li>including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertir</li> <li>Propose to add perfs at 4315, 16, 17, 18, 4 4429.5, 30, 30.5, 32, 32,5, 33 and acidize perforated intervals.</li> <li>Subsurface Safety Valve: Manu. and Type</li></ul>	addrectionally drilled, give subsurface locations and hent to this work.)* add, 45, 50, 50.5, 52, 52.5, 53, interval and then frac all DECERTYEND HOV 3 1982 CL & ESS MINISTIC RECEIVICE RECTICE RECEIVICE
<ul> <li>including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertir</li> <li>Propose to add perfs at 4315, 16, 17, 18, 4 4429.5, 30, 30.5, 32, 32,5, 33 and acidize perforated intervals.</li> <li>Subsurface Safety Valve: Manu. and Type</li></ul>	addrectionally drilled, give subsurface locations and hent to this work.)* add, 45, 50, 50.5, 52, 52.5, 53, interval and then frac all DECERTYEND HOV 3 1982 CL & ESS MINISTIC RECEIVICE RECTICE RECEIVICE
<ul> <li>including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertir</li> <li>Propose to add perfs at 4315, 16, 17, 18, 4 4429.5, 30, 30.5, 32, 32,5, 33 and acidize perforated intervals.</li> <li>Subsurface Safety Valve: Manu. and Type</li></ul>	addrectionally drilled, give subsurface locations and hent to this work.)* add, 45, 50, 50.5, 52, 52.5, 53, interval and then frac all DECERTYEND HOV 3 1982 CL & ESS MINISTIC RECEIVICE RECTICE RECEIVICE
including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertir. Propose to add perfs at 4315, 16, 17, 18, 4 4429.5, 30, 30.5, 32, 32,5, 33 and acidize perforated intervals. Subsurface Safety Valve: Manu. and Type	a directionally drilled, give subsurface locations and hent to this work.)* a 344, 45, 50, 50.5, 52, 52.5, 53, interval and then frac all DECOTING 1982 CON 3 1982 CON 3 1982 CON 3 1982 CON 5 1982 Coordinator November 1, 1982 Coordinator November 1, 1982
<pre>including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertir Propose to add perfs at 4315, 16, 17, 18, 4 4429.5, 30, 30.5, 32, 32,5, 33 and acidize perforated intervals.</pre> Subsurface Safety Valve: Manu. and Type Is. I hereby certify that the foregoing is true and correct SIGNED	a directionally drilled, give subsurface locations and hent to this work.)* a 344, 45, 50, 50.5, 52, 52.5, 53, interval and then frac all DECOTING 1982 CON 3 1982 CON 3 1982 CON 3 1982 CON 5 1982 Coordinator November 1, 1982 Coordinator November 1, 1982
including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertir. Propose to add perfs at 4315, 16, 17, 18, 4 4429.5, 30, 30.5, 32, 32,5, 33 and acidize perforated intervals. Subsurface Safety Valve: Manu. and Type	a directionally drilled, give subsurface locations and hent to this work.)* a 344, 45, 50, 50.5, 52, 52.5, 53, interval and then frac all DECOTING 1982 CON 3 1982 CON 3 1982 CON 3 1982 CON 10 NOTE MINUTE 10 NOTE PROVIDE NOTE PROVIDE NOTE PROVIDE NOTE PROVIDE NOTE PROVIDE NOTE PROVIDE NOTE PROVIDE NOTE Coordinator November 1, 1982
<pre>including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertir Propose to add perfs at 4315, 16, 17, 18, 4 4429.5, 30, 30.5, 32, 32,5, 33 and acidize perforated intervals.  Subsurface Safety Valve: Manu. and Type</pre>	a directionally drilled, give subsurface locations and hent to this work.)* a344, 45, 50, 50.5, 52, 52.5, 53, interval and then frac all DECENTED INVERTICE NOTE MINUTE IC NOTE NICE NOTE Set @ XICO FOR COORDINATION FOR THE SET @ XICO DATE
including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertir Propose to add perfs at 4315, 16, 17, 18, 4 4429.5, 30, 30.5, 32, 32,5, 33 and acidize perforated intervals. Subsurface Safety Valve: Manu. and Type	a directionally drilled, give subsurface locations and hent to this work.)* a344, 45, 50, 50.5, 52, 52.5, 53, interval and then frac all DECENTED INVERTICE NOTE MINUTE IC NOTE NICE NOTE Set @ XICO FOR COORDINATION FOR THE SET @ XICO DATE

67. AN 187

-