

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Artesia, NM 88210

NM Oil Cons. Commission
Permit Instructions on re-
lease and
Artesia, NM 88210

Form approved.
Budget Bureau No. 1004-011
Expires August 31, 1985
LEASE DESIGNATION AND SERIAL NO.

NM-16069

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐
2. NAME OF OPERATOR
McClellan Oil Corporation
3. ADDRESS OF OPERATOR
P.O. Drawer 730, Roswell, NM 88202
4. LOCATION OF WELL (Report location clearly and in accordance with all State requirements.
See also space 17 below.)
At surface

1528' FSL & 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether OF, RT, GR, etc.)

3598' GR

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Coyote Federal

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 12-T8S-R24E

12. COUNTY OR PARISH 13. STATE

Chaves

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) casing & cement

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

6/10/87: Spudded with 12 1/4" bit.

6/13/87: Ran 19 joints, 868' of 8-5/8", 23 lb. casing. Cemented using Halliburton with 100 sx Thixset 3% CaCl, 150 sx Halliburton Lite 2% CaCl - 1/4# Flocele, and 200 sx Class "C" 2% CaCl. Plug down at 8:00 pm. Ran temp. survey, TOC - 250'. 1" with 150 sx Class "C" 3% CaCl. Circulated 15 sx. Nipple up BOP's. Tested 1000 psi for 30 minutes. Drill out with 7-7/8" bit.



18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Drilling Engineer

DATE

6/15/87

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
PETER W. CHESTER
DATE

JUN 23 1987

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

*See Instructions on Reverse Side