

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petroleum Corp</u>		Lease <u>Skink "SK" State</u>		Well # <u>3</u>	
Location of Well	Unit <u>660N 1650W C</u>	Section <u>32</u>	Township <u>7</u>	Range <u>26</u>	County <u>Chaves</u>
Drilling Contractor	<u>L+M #2</u>		Type of Equipment <u>Rotary</u>		

* witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
13/4 12 1/4	8 5/8 8 5/8	24 24.5 # J-55	New	950	Suff to Circ
7 7/8	4 1/2	9.5 #			350 SX

Casing Data:

Surface 28 joints of 8 5/8 inch 24 # Grade J-55

yes (Approved) (Rejected)

Inspected by BW Weaver date 6-20-82

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 200

Type of Shoe used Tex-Pat Float collar used Insert Btm 3 jts welded yes

TD of hole 960 Set 965 Feet of 8 5/8 Inch 24 # Grade J-55

New ~~used~~ csg. @ 965 with ~~200~~ 200 sacks neat cement around shoe

+ 400 sax Henco lite additives 1/4 Flo Sol #5 6ilcowite 2% cc

Plug down @ 11:15 (AM) (PM) Date 6-20-82

Cement circulated yes No. of Sacks 100

Cemented by Henco Witnessed by BW Weaver

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: