

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.O.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO

O. C. D.  
ARTESIA, OFFICE

Form C-103  
Revised 10-1-73

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>	
5. State Oil & Gas Lease No. LG-338	
7. Unit Agreement Name	
8. Farm or Lease Name Eureka UK State	
9. Well No. 1	
10. Field and Pool, or Wildcat Wildcat Abo	
12. County Chaves	

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

OIL  
WELL ☐

GAS  
WELL ☒

OTHER-

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER D 660 FEET FROM THE North LINE AND 660 FEET FROM

THE West LINE, SECTION 20 TOWNSHIP 10S RANGE 26E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3776.5' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

INFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

WELL OR ALTER CASING ☐

OTHER ☐

CASING TEST AND CEMENT JOBS ☒

OTHER ☐

2. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 14-3/4" hole 2:30 AM 6-3-82. Ran 24 joints of 10-3/4" 40.5# J-55 casing set at 942'. 1-notched guide shoe at 942'. Insert float at 902'. Cemented w/600 sacks Halliburton Lite, 1/4# flocele and 2% CaCl. Tailed in w/200 sacks Class "C" 2% CaCl. Compressive strength of cement - 1250 psi in 12 hours. PD 8:25 AM 6-5-82. Bumped plug to 800 psi, released pressure and float held okay. Cement circulated 50 sacks to pit. WOC. Drilled out 2:30 PM 6-6-82. WOC 18 hours and 5 minutes. Nippled up and tested to 1000 psi, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

*Lyntia Goodlett*

TITLE Engineering Secretary

DATE 6-18-82

*Mike Williams*

TITLE OIL AND GAS INSPECTOR

DATE JUN 25 1982

CONDITIONS OF APPROVAL, IF ANY: