

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO

RECEIVED

JUL 2 1982

O. C. D.

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT DISCOVERY. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Cibola Energy Corporation ✓		8. Farm or Lease Name CB Plains
3. Address of Operator P.O. Box 1668, Albuquerque, New Mexico 87103		9. Well No. 1
4. Location of Well UNIT LETTER <u>M</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>17</u> TOWNSHIP <u>10S</u> RANGE <u>28E</u> NMPM.		10. Field and Pool, or Wildcat Und. Race Track San Andre
15. Elevation (Show whether DF, RT, GR, etc.) 3772.7		12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-18-82 Spudded at 7:00 am.

6-25-82 Ran 304' of 8 5/8" 24# casing. Regular texas pattern guide shoe and insert float. Cemented with 200 sacks Class C Cement with 2% CaCl, 5 sacks quik seal, 5 sacks gel. Circulated cement to surface. Bumped plug 500#. WOC 18 hours. Continued to drill.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Amrita Y. Chizil TITLE Drilling Secretary DATE 6-29-82

APPROVED BY W. A. Gressitt TITLE SUPERVISOR, DISTRICT II DATE JUL 2 1982

CONDITIONS OF APPROVAL, IF ANY: