Core 1973 UNITED STATES ATLOGIA, IM 88210 DEPARTMENT OF THE INTERIOR CEOLOGICAL SURVEY 5. LEASE SUNDRY NOTICES AND REPORTS ON WELLS On and the three of the formation of the depension of plug back to a different well well with the of the formation of the depension of plug back to a different well well well well with the of the formation of the depension of plug back to a different well well well well well well well well	UNITED STATES AT Set 3. JM 68210 DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY SUNDERY NOTICES AND REPORTS ON WELLS Automatic definition of the proposable to add or a deepen or place back to a difference J. UNIT AGREEMENT NAME J. UNIT AGR	NM OIL CONS. COMMIS Drawer DD	SION Form Approved. Budget Bureau No. 42-R1424
		UNITED STATES Artesia, NM 88210	
GEOLOGICAL SUMITY SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS Colspan="2">Colspan="2" Colspan="2" <td>COUCONNEL SUMPER</td> <td>DEPARTMENT OF THE INTERIOR</td> <td></td>	COUCONNEL SUMPER	DEPARTMENT OF THE INTERIOR	
SUNDRY NOTICES AND REPORTS ON WELLS. GB: out-at the home to product of and the deepen or plug back to a different of the deepen or plug back to a different of the deepen or plug back to a different of the deepen of th	SUNDRY NOTICES AND REPORTS ON WELLS Drade and Phylore By Decomparity of the construction of the provide and p	GEOLOGICAL SURVEY	
Characterized is from the propendials is will not deepen or plug back to a different Characterized is from the propendials is will not deepen or plug back to a different Characterized is different to a stress and propendials. Concentron of well (RECONTINGENER) CONCENTOR WELL NEW ALS C., A FEESIA, NM 88210. CONCENTOR WELL REPORT LOCATION CLEARY, See space 17 below) AT SUFFACE: 1980 FSL & 1980 FWL, Sec.14-65-251 AT TOP PROD. INTERVAL: AT TOTAL DEPTH: CONTENT OF WELL REPORT LOCATION CLEARY, See space 17 below) AT SUFFACE: 1980 FSL & 1980 FWL, Sec.14-65-251 AT TOP PROD. INTERVAL: AT TOTAL DEPTH: CONTENT ACCENTRY AND SUPPLY OR INTERVAL: AT TOTAL DEPTH: CONTENT ACCENTRY AND SUPPLY OR INTERVAL: REPART SHUT OF FRACTURE TREAT SUBSEQUENT WELL NO. CONTENT ACCENTRY SUBSEQUENT WAY 25 1983 CONTENT ACCENTRY AND SUPPLY OR THE SUBSEQUENT MAY 25 1983 CONTENT ACCENTRY AND SUPPLY OR THE SUBSEQUENT MAY 25 1983 CONTENT ACCENTRY AND SUPPLY OR THE SUBSEQUENT MAY 25 1983 CONTENT ACCENTRY AND SUPPLY OR THE SUBSEQUENT SUBSEQUENT MAY 25 1983 CONTENT ACCENTRY AT SUBARCE I SUBSEQUENT MAY 25 1983 CONTENT ACCENTRY AT TOTAL DEPTH: CONTENT ACCENTRY AT TOTAL DEPTH: CONTENT ACCENTRY AT TOTAL SUBSEQUENT AT TOR ADDUCK REPARY WELL CONTENT ACCENTRY AT TOR ADDUCK ATTERNATION ATTERNATION ATTERNATION ATTERNATION ATTERNATION ATTERNATION ATTERNATION ATTERNATION ATTERNATION ATTE	De and, we mus form to reproduce your of the determined production of the determined	CUNDRY NOTICES AND REPORTS ON WELLS	
Little of the second		Do not use this form for proposals to drill or to deepen or plug back to a different	ILIN 0.1 1002
weil LN weil A other 2. NAME OF OPERATOR 3. ADDRESS OF OPERATOR 2.1. Control of Well (REPORT LOCATION CLEARLY, See space 17 below.) 207 South 4ch SC., Artesia, NM 88210. 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below.) AT TOP PRODEINTER BOX TO INDICATE NATURE OF NOTICE. 18. OFFECT OF APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER BOAT OF INDICATE NATURE OF NOTICE. REQUEST FOR APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REQUEST FOR APPROPRIAT BOX TO INDICATE NATURE OF NOTICE. REQUEST FOR APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. NMAY 25 1983 NULTIPLE COMPETE PULL OR ALTER CASING WULTIPLE COMPETE OPERATOR BOSWELL, NEW MEXICO 10. DESCRIPT OPERATORS 11. DESCRIPT OPERATOR 12. DESCRIPT OPERATORS (Clearly state of multiple completion or zone distants and group periment dates, and group periment	well L well A ether Artesta of operation 2. NAME of OPERATOR Artesta, OFHCE 2. NAME of OPERATOR Artesta, OFHCE 2. NORMESS OF OPERATOR Artesta, Artesta, NH 88210. 2. Occation of WillCAT NAME Suburdation of Well (REPORT IOCATION CLEARLY, See space 1) below, Artesta, And Survey or Artesta, And Survey or Artesta, Artesta, OFHCE Artesta, Artostic Box to INDICATE NATURE OF NOTICE, In FILD OPENATION Stort of Arter Casing Subscription REPORT, OR OFHER EDIA Subscription REQUEST FOR APPROVAL TO SUBSEQUENT REFORM OR OFHERE BEST 1' GR PULL OR ALTER CASING MAY 25 1983 MULTPLE COMPLETE BEST 1' GR PULL OR ALTER CASING MAY 25 1983 MULTPLE COMPLETE BEST 1' GR PULL OR ALTER CASING MAY 25 1983 MULTPLE COMPLETE DEFATIONS (Schow DF, KDB, AND WD) 2015 Extended 14-3/4" hole 7:15 AM 5-18-83. Set 40' of 20" conductor pipe. Ran 23 joints 10-3/4" A0.59 J-35 crasting set 904'. L-Texas Pattern notched guide shoce set '.'. Insert float set 804'. Cemented w/ADO sacks Pacesetter Lite, 1/4#/sack 10-3/4" A0.59 J-35 Crasting set 904'. L-Texas Pattern notched guide of 0000 psi for minutes of 11 hours. PD 4:15 PM 5-19-83. Subgroup co	servoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME JUN UI 1983 Powers OL Federal
2. NAME OF OPERATOR Yates Petroleum Corporation 2. ADDRESS OF OPERATOR 2.07 South 4th St., Artesia, NM 88210. 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space in beyon, at subface: 1980 FSL & 1980 FWL, Sec.14-65-25E At TOP PROD. INTERVAL: At TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT SUBSEQUENT SUBSEQUENT WAY 25 1983 NM Y 25 105 NUTFRE COMPLETE 10. DECOMPLETE 11. DECOMPLETE 12. CONTYON OF KDB, AND WD) 3855.1' GR SUBSEQUENT MAY 25 105 NUTFRE COMPLETE 13. ELEVATIONS (SHOW DF, KDB, AND WD) 3855.1' GR 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3855.1' GR SUBSEQUENT MAY 25 105 NUTFRE COMPLETE 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3855.1' GR 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE 17. DESCRIBE PROPOSED ON COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates. Including estimuted date of stating any proposed work. If well is directionally diffied, give subsurface locations and measured and true vertical depths for all markers and Compse pertinent to this work.)' 10. J AFCRE PROPOSED ON COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates. Including estimuted date of stating any proposed work. If well is directionally diffied, give subsurface locations and measured and true vertical depths for all markers and comes pertinent to this work.'' 10. JA('' 40.5f) J-55 chasing set 904'. I. TEXAS Pattern notched guide shoe set 11. Secont 10. SM 5-20-83. WOR OD as acks Clears ''' ZC GACL2. Compressive strength Cement - 1250 psi in 12 hours. PD 4:15 PM 5-19-83. Bumped plug to 1000 psi, 11. Hereby certify that the foregoing is true and correct Production SogeD L. A. L. L. WW MEXICO ACCEPTED FOR RECORD's space for Federal of State office USU APPROVED BY (ORLIC, SGD.) DAYID B, CLASS COMMITIONS OF APPROVED SCIENCE SPACE for Federal of State office U	2. NAME OF OPERATOR Tates Petroleum Corporation 2. ADDRESS OF OPERATOR 2. OZORTON OF WELL (REPORT LOCATION CLEARLY. See space 1 below) at SUPRATE 1980 FXL, Artesia, NN 88210. 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 1 below) at SUPRATE 1980 FXL, Steches Space 1 at TOTAL DEPTH: 4. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. TOTO TA CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. THE CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. 5. CHECK APPROPRIATE BOX TO INDICATE STATE OF S	- u A athor	9. WELL NO. O. C. D.
A ADDRESS OF OPERATOR 207 South 4th St., Artesia, NM 88210 4 LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 AT SUBFACE: 1980 FSL & 1980 FVL, Sec.14-6S-25E AT TOP PROD. INTERVAL: AT TOTAL DEFTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE: REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: TSY WATER SUNJOFT PRACTURE TREAT SUBSEQUENT DUL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ARANOON' ADDRESS CONSERVAL TO: TSY WATER CONES ARANOON' ADDRESS CONSERVAL TO: TSY WATER SUNJOFT REPORT, OR OTHER DATA REPORT, DR	ADDRESS OF OPERATION Peccos Slope Abo 207 South 4th St., Artesia, NM 88210. Peccos Slope Abo 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 Dit K, Sec. 14-16S-R25E AT SUFACT: 1980 FSL. & 1980 FML, Sec.14-6S-25E Art APROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REPORT, OR OTHER DATA SUBSEQUENT NEEVENT FOR APPROVAL TO: SUBSEQUENT REVENT FOR APPROVAL TO: SUBSEQUENT NULL OR ATTER CASING MAY 25 1983 MULT PLE COMPETER DL & GAS MONON* REPARENT OF LOCATIONS (Clearly state all pertinent detais, and give pertinent dates. Including estimated date of stating any proposed work. If well is directionally drilled, give subsurface locations and measure and true vertice deptis for all markers and zones pertinent to this work.)* ID-3/4" hole 7:15 AN 5-18-83. Set 40° of 20" conductor pipe. Ran 23 joints 10-3/4" hole 7:15 AN 5-18-83. Set 40° do 20" conductor pipe. Ran 23 joints 10-3/4" 40.5# J-55 cnsing set 904*. I-TEXIS Pattern notched guide shoe set * '. Insert float set 864'. Comented w/400 sacks Pacesetter Lite, 1/4#/sack ID-3/4" hole 7:15 AN 5-18-83. Well PM 5-19-83. Bumped plug to 1000 psi, for minutes, 0K. Reduced hole to 7-7/8". Drilled plug and resumed dri		ARTESIA, OFFICE
207 South 4th St., Artesia, NM 88210 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) Artesia, NM State Artesia, NM State Artesia, NM State Artesia, NM State Artesia, State Bister, State	207 South 4th St., Artesta, NM 88210. 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below). AT SURFACE: 1980 FSL & 1980 FWL, Sec.14-65-25E AT TOP PROPORIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: IS. CLECKAPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT WAY 2.5 1983 NOT OR ACIDIZE CANAGE ZONES SAGANDON' Control of ACIDIZE CHANGE ZONES ARAMDON' Control of ACIDIZE CHANGE ZONES ADAMONO' Control of ACIDIZE CHANGE ZONES ADAMONO' Control of ACIDIZE CHANGE ZONES ADAMONO' Control of ACIDIZE CHANGE ZONES ADAMONO' Control of ACIDIZE CHANGE ZONES CANAGE ZONES COMPLETE CHANGE ZONES COMPLETE CHANGE ZONES CANAGE ZONES CANAGE ZONES CANAGE ZONES CANAGE ZONES COMPLETE CHANGE ZONES CANAGE ZONES COMPLETE CHANGE ZONES CANAGE ZONES COMPLETE COM		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) WARA A TOP PROD. INTERVAL: AT TOTAL DEPTH: Unit K, Sec. 14-65-25E 12. COUNTY OF PARISH 13. STATE Chaves NM 13. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA I.4. API NO. 14. API NO. I.5. ELEVATIONS (SHOW OF, KDB, AND WD) 3855.1' GR 14. API NO. I.5. ELEVATIONS (SHOW OF, KDB, AND WD) 3855.1' GR 15. OUTER DATA WAY 25 1933 REPORT, OR OTHER DATA WAY 25 1933 REPORT, OR OTHER DATA WAY 25 1933 REPORT, OR OTHER DATA WAY 25 1933 REQUEST FOR APPROVAL TO FRACTURE TREAT WAY 25 1933 REQUEST FOR APPROVAL TO TEST WATER SHUT OF WAY 25 1933 REPORT, WELL REPORT, OR OTHER DATA WAY 25 1933 MULT PLE COMPLETE WAY 25 1933 ONL & GAS ROSWELL, NEW MEXICO 10. DESCHIE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates. Including estimated date of stating any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertial deptis for an once see of norm 9-330.3 10. DESCHIE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates. Including estimated date of stating any proposed work. If well is directionally drilled, give subsurface locations	4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below). Unit K., Sec. 14-T6S-R25E Unit K., Sec. 14-T6S-R25E AT TOP PROD. INTERVAL: AT TOTAL DEPTH: Int K., Sec. 14-T6S-R25E AT COP PROD. INTERVAL: AT TOTAL DEPTH: Int K., Sec. 14-T6S-R25E 16. CHCCK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. Int K., Sec. 14-T6S-R25E 11. CALCK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. Int K., Sec. 14-T6S-R25E 12. COUNTY OR PARISHING Int K., Sec. 14-T6S-R25E 13. CALCK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. Int K., Sec. 14-T6S-R25E 14. API NO. Int K., Sec. 14-T6S-R25E 14. API NO. Int K., Sec. 14-T6S-R25E 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3855.1' GR REQUEST FOR APPROVAL TO: TEST WATER SHUTOFF SUBSEQUENT Int K., Sec. 14-T6S-R25E Int K., Sec. 14-T6S-R25E Int K., Sec. 14-T6S-R25E Int K., Sec. 14-T6S-R25E Int K., Sec. 14-T6S-R25E Int K., Sec. 14-T6S-R25E REQUEST FOR APPROVAL TO: TEST WATER SHUTOFF Int K., Sec. 14-T6S-R25E RECORD ATTER SHUTOFF Int K., Sec. 14-T6S-R25E RECORD ATTER SHUTOFF Int K., Sec. 14-T6S-R25E Int K., Sec. 14-T6S-R25E Int K., Sec. 14-T6S-R25E Int K., Sec. 14-T6S-R25E Int K., Sec. 14		11. SEC., T., R., M., OR BLK. AND SURVEY OR
below3, AT SURFACE: 1980 FSL & 1980 FWL, Sec.14-65-25E 12. COUNTY OR PARISH 13. STATE AT TOTA DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA 14. API NO. 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA 5. ELEVATIONS (SHOW DF, KDB, AND WD) 3855.1' GR REQUEST FOR APPROVAL TO: SUBSEQUENT SUBSEQUENT MAY 25 1983 MAY 25 10	below) AT SURACE: 1980 FSL & 1980 FWL, Sec.14-6S-25F 12. COUNTY OR PARISH 13. STATE AT TOTA LOETH: 14. API NO. 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3855.1' GR NEQUEST FOR APPROVAL TO: REPORT, OR OTHER DATA SUBSEQUENT FOR APPROVAL TO: REPORT, OR OTHER DATA MAY 25 1983 OTHER TO	4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	
AT TOP PROD. INTERVAL: AT TOTA DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TRAT SHORT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING WULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates. ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates. Including estimated date of stating may proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all matters and zones pertinent to this work.)* Added 14-3/4" hole 7:15 AM 5-18-83. Set 40' of 20" conductor pipe. Ran 23 joints 10-3/4" 40-5% J-55 cassing set 904'. 1-Texas Pattern notched guide shoe set 4'. Insert float set 864'. Cemented w/400 sacks Placestter Lite, 1/4#/sack 110-32/4" using 2. Tailed in w/300 sacks Class "C" 2% CaCl2. Compressive strength leased pressure and float held okay. Cement circulated 50 sacks. to pit. WOC. 11ed out 10:15 AM 5-20-83. WOC 18 hours. Nippled up and tested to 1000 psi, 10 class of all the low of the subsurface for all matters and correct Production stoppet Latter Manu. and Type Subsurface Safety Valve: M	AT TOP PROD. INTERVAL: AT TOTAL DEPTH: IS. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT SUBSEQUENT SUBSEQUENT WAY 25 1983 WAY 2	below.) AT SUBFACE 1980 FSL & 1980 FWL, Sec.14-6S-25E	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3555.1' GR REQUEST FOR APPROVAL TO: TEST WATER SHUTOFF FRACTURE TRAT SHOOT OR ACIDIZE CHARGE ZONES ABANDON' ONLE COMPLETE CHANGE ZONES ABANDON' 10. BESCRIBE PROPOSED OR COMPLETED OFERATIONS (Clearly state all pertinent details, and give pertinent dates. Including estimated due to starting may proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent dots. Start of the work.)' 10. JGK 40.5 # J-55 cashing set 904'. I -Texas Pattern notched guide shoe set 4'. Insert float set 864'. Cemented w/400 sacks Pacesetter Lite, 1/4#/sack 10.3 // 40.5 # J-55 cashing set 904'. I -Texas Pattern notched guide shoe set 4'. Insert float set 864'. Cemented w/400 sacks Pacesetter Lite, 1/4#/sack 10.3 // 40.5 # J-55 cashing set 904'. I -Texas Pattern notched guide shoe set 4'. Insert float set 864'. Cemented w/400 sacks Pacesetter Lite, 1/4#/sack 11. Bescribe proposition of the work of the work. I well subsurface locations and measured and true vertical depths for all markers and zones pertinent details, and give pertinent dates. Including stimated hole to 7-7/8". Drilled plug and tested to 1000 psi, 10-3/4" Wolf - 20-83. WOC 18 hours. Nippled up and tested to 1000 psi for minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling. Subsurface Safety Valve: Manu. and Type Set @	16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT SUBACT SUBSEQUE	AT TOP PROD. INTERVAL:	
REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT TRAT SHOOT OR ACIDIZE PULL OR ACIDIZE PULL OR ALTER CASING UTIPLE COMPLETE ULL OR ALTER CASING MULTIPLE COMPLETE OF ADAPT OF THE COMPLETE OF ADAPT OF THE COMPLETE OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) ² idded 14-3/4" hole 7:15 AM 5-18-83. Set 40' of 20" conductor pipe. Ran 23 joints 10-3/4" 40.5% J-55 casing set 904'. L-Texas Pattern notched guide shoe set 4'. Insert float set 864'. Cemented w/400 sacks Class "C" 2% CaCl2. Compressive strength cement - 1250 psi in 12 hours. PD 4:15 PM 5-19-83. Bumped plug to 1000 psi, leased pressure and float held okay. Cement circulated 50 sacks. to pit. WOC. illed out 10:15 AM 5-20-83. WOC L8 hours. Nippled up and tested to 1000 psi for minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling. Subsurface Safety Valve: Manu. and Type ACCEPTED FOR RECORD: space for Federal of State office use) APPROVED BY (ORIG. SGD.) DAVID B. CLASS CONDITIONS of APPROVAL	REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: TEST WATER SHUTOFF FRACTURE TEAT SHOOT OR ACIDIZE WULL TREE CASING WULL TREE CASING WULL TREE COMPLETE Contance Zones ABANDON' 10. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* dded 14-3/4" hole 7:15 AM 5-18-83. Set 40' of 20" conductor pipe. Ran 23 joints 10-3/4" 40.58 J-55 casing set 904'. 1-Texas Pattern notched guide shoe set '. Insert float set 864'. Cemented w/A00 sacks Pacesetter Lite, 1/4#/sack loseal, 3% CaCl2. Tailed in w/300 sacks Class "C" 2% CaCl2. Compressive strength cement - 1250 psi in 12 hours. PD 4:15 PM 5-19-83. Bumped plug to 1000 psi, eased pressure and float held okay. Cement circulated 50 sacks. to pit. WOC. Iled out 10:15 AM 5-20-83. WOC 18 hours. Nippled up and tested to 1000 psi for minutes, 0K. Reduced hole to 7-7/8". Drilled plug and resumed drilling. Subsurface Safety Valve: Manu. and Type Set @Ft. 18. Thereby certify that the foregoing is true and correct Production supper (ORIG, SGD) DAVID R. CLASS Date APPROVED BY (ORIG, SGD) DAVID R. CLASS Date APPROVED BY (ORIG, SGD) DAVID R. CLASS Date CONDITIONS or APPROMA		14. API NO.
REQUEST FOR APPROVAL TO: SUBSEQUENT SUBSEQUENT Image: Construction of the second	REQUEST FOR APPROVAL TO. SUBSEQUENT Image: Control of the subsection of the s		15. ELEVATIONS (SHOW DF, KDB, AND WD) 3855.1' GR
FRACTURE TREAT	FRACTURE TREAT SHOOT OR ACIDIZE MAY 25 1983 NAY 25 1983 NAY 25 1983 NAY 25 1983 NAY 25 1983 NAY 25 1983 NAY 25 1983 NAY 25 1983 NAY 25 1983 NAY 25 1983 NAY 25 1983 NAY 25		WED .
SHOOT OR ACIDIZE ALL MAY 25 1983 Charge on Form 9-330.) MULL OR ALTER CASING MAY 25 1983 Charge on Form 9-330.) MULTIPLE COMPLETE OIL & GAS BANDON* OIL & GAS ABANDON* OIL & GAS I'. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* idded 14-3/4" hole 7:15 AM 5-18-83. Set 40' of 20" conductor pipe. Ran 23 joints 10-3/4" 40.5# J-55 casing set 904". 1-Texas Pattern notched guide shoe set 4'. Insert float set 864'. Cemented w/400 sacks Pacesetter Lite, 1/4#/sack iloseal, 3% CaCl2. Tailed in w/300 sacks Class "C" 2% CaCl2. Compressive strength cement - 1250 psi in 12 hours. PD 4:15 PM 5-19-83. Bumped plug to 1000 psi, leased pressure and float held okay. Cement circulated 50 sacks. to pit. WOC. illed out 10:15 AM 5-20-83. WOC 18 hours. Nippled up and tested to 1000 psi for minutes, 0K. Reduced hole to 7-7/8". Drilled plug and resumed drilling. Subsurface Safety Valve: Manu. and Type 18. Intereby certify that the foregoing is true and correct Production signed Coll Minute ACCEPTED FOR RECORD is space for Federal or State office use	SHOOT OR ACIDIZE ALL MAY 25 1983 INTER CASING MEPAIR WELL MAY 25 1983 INTER CASING MAY 25 1983 INTER CASING MULTIPLE COMPLETE MAY 25 1983 INTER CASING INTER CASING INTER CASING MULTIPLE COMPLETE INTER CASING INTER CASING INTER CASING INTER CASING Intel completion or zone change on Form 9-330.1 INTER CASING INTER CASING INTER CASING Intel completion or zone change on Form 9-330.1 INTER CASING INTER CASING INTER CASING Intel completion or zone change on Form 9-330.1 INTER CASING INTER CASING INTER CASING Intel completion or zone change on Form 9-330.1 INTER CASING INTER CASING INTER CASING Intel completion or zone change on Form 9-330.1 INTER CASING INTER CASING INTER CASING Intel completion or zone change on Form 9-330.1 INTER CASING INTER CASING INTER CASING Intel completion or zone completion or zone completion or zone change on Form 9-330.1 INTER CASING INTER CASING Inde completion or zone co		
MAY 25 1983 change on Form 9-330.) MULTPLE COMPLETE ONL & GAS MULTUPLE COMPLETE ONL & GAS ABANDON* ONL & GAS (other) ROSWELL, NEW MEXICO 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical deptits for all markers and zones pertinent to this work.)* vidded 14-3/4" hole 7:15 AM 5-18-83. Set 40' of 20" conductor pipe. Ran 23 joints 10-3/4" 40.5# J-55 casing set 904'. 1-Texas Pattern notched guide shoe set 4'. Insert float set 864'. Cemented w/400 sacks Pacesetter Lite, 1/4#/sack 10-seal, 3% CaCl2. Tailed in w/300 sacks Class "C" 2% CaCl2. Compressive strength cement - 1250 psi in 12 hours. PD 4:15 PM 5-19-83. Bumped plug to 1000 psi, leased pressure and float held okay. Cement circulated 50 sacks. to pit. WOC. filled out 10:15 AM 5-20-83. WOC 18 hours. Nippled up and tested to 1000 psi for minutes, 0K. Reduced hole to 7-7/8". Drilled plug and resumed drilling. Subsurface Safety Valve: Manu. and Type Set @Ft. 18. Thereby certify that the foregoing is true and correct Production state office use) ACCEPTED FOR RECORD is space for Federal or State office use) APPROVED BY (ORIG, SGD.) DAVID B. GLASS DATE APPROVED BY (ORIG, SGD.) DAVID B. GLASS DATE ROSWELL, NEW MEXICO DATE	PULL OR ALTER CASING MAY 2 5 1983 change on Form 9-330.1 MULTIPLE COMPLETE OIL & GAS MULTIPLE COMPLETE OIL & GAS MORENTS OIL & GAS ABANDON* OIL & GAS Including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* dded 14-3/4" hole 7:15 AM 5-18-83. Set 40' of 20" conductor pipe. Ran 23 joints 10-3/4" 40.5% J-55 casing set 904'. 1-Texas Pattern notched guide shoe set '. Insert float set 864'. Cemented w/400 sacks Pacesetter Lite, 1/4#/sack loseal, 3% CaCl2. Tailed in w/300 sacks Class "C" 2% CaCl2. Compressive strength cement - 1250 psi in 12 hours. PD 4:15 PM 5-19-83. Bumped plug to 1000 psi, eased pressure and float held okay. Cement circulated 50 sacks. to pit. WOC. 11ed out 10:15 AM 5-20-83. WOC 18 hours. Nippled up and tested to 1000 psi for minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling. Subsurface Safety Valve: Manu. and Type Set @Ft. 18. Thereby certify that the foregoing is true and correct production sugges of control pattern of the space for Federal or State office use) DATE ACCEPTED FOR RECORD: space for Federal or State office use) DATE APPROVED BY (ORLIG. SCD.) DAVID R. CLASS DATE CONDITIONS of APPROMARY 3"I 1983 DATE <	SHOOT OR ACIDIZE	
MULTIPLE COMPLETE OIL & GAS ABANDON' ROSWELL, NEW MEXICO 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* rdded 14-3/4" hole 7:15 AM 5-18-83. Set 40' of 20" conductor pipe. Ran 23 joints 10-3/4" 40.5% J-55 casing set 904'. 1-Texas Pattern notched guide shoe set 4'. Insert float set 864'. Cemented w/400 sacks Pacesetter Lite, 1/4#/sack 110seal, 3% CaCl2. Tailed in w/300 sacks Class "C" 2% CaCl2. Compressive strength cement - 1250 psi in 12 hours. PD 4:15 PM 5-19-83. Bumped plug to 1000 psi, leased pressure and float held okay. Cement circulated 50 sacks. to pit. WOC. 111ed out 10:15 AM 5-20-83. WOC 18 hours. Nippled up and tested to 1000 psi for minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling. Subsurface Safety Valve: Manu. and Type Set @Ft. 18. I hereby certify that the foregoing is true and correct production DATE5-23-83	MULTIPLE COMPLETE OIL & GAS CHANGE ZONES BOSWELL, NEW MEXICO (other) ROSWELL, NEW MEXICO 11. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertiment details, and give pertinent dates, metuding estimated date of stating any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* dded 14-3/4" hole 7:15 AM 5-18-83. Set 40' of 20" conductor pipe. Ran 23 joints 10-3/4" 40.5# J-55 casing set 904'. 1-Texas Pattern notched guide shoe set '. Insert float set 864'. Cemented w/400 sacks Pacesetter Lite, 1/4#/sack loseal, 3% CaCl2. Tailed in w/300 sacks Class "C" 2% CaCl2. Compressive strength cement - 1250 psi in 12 hours. PD 4:15 PM 5-19-83. Bumped plug to 1000 psi, eased pressure and float held okay. Cement circulated 50 sacks. to pit. WOC. 11ed out 10:15 AM 5-20-83. WOC 18 hours. Nippled up and tested to 1000 psi for minutes, 0K. Reduced hole to 7-7/8". Drilled plug and resumed drilling. Subsurface Safety Valve: Manu. and Type Set @Ft. 18. I hereby certify that the foregoing is true and correct production stope (REPAIR WELL \square MAY 25	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
ABANDON* (other) ROSWELL, NEW MEXICO 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 19. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 10. J/4" 40.5# J-55 casing set 904'. 1-Texas Pattern notched guide shoe set 10. J/4" 40.5# J-55 casing set 904'. 1-Texas Pattern notched guide shoe set 10. Insert float set 864'. Cemented w/400 sacks Pacesetter Lite, 1/4#/sack 110seal, 3% CaCl2. Tailed in w/300 sacks Class "C" 2% CaCl2. Compressive strength cement - 1250 psi in 12 hours. PD 4:15 PM 5-19-83. Bumped plug to 1000 psi, leeased pressure and float held okay. Cement circulated 50 sacks. to pit. WOC. 111ed out 10:15 AM 5-20-83. WOC 18 hours. Nippled up and tested to 1000 psi for minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling. Subsurface Safety Valve: Manu. and Type Subsurface Safety Valve: Manu. and Type ACCEPTED FOR RECORD is space for Federal or State office use) ACCEPTED FOR RECORD is space for Federal or State office use) APPROVED BY (ORIG. SGD.) DAVID B. CLASS CONDITIONS OF APPROMAY' 3*1 1983 ROSWELL, NEW MEXICO	ABANDON* (other) ROSWELL, NEW MEXICO 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* dded 14-3/4" hole 7:15 AM 5-18-83. Set 40' of 20" conductor pipe. Ran 23 joints 10-3/4" 40.5# J-55 casing set 904'. 1-Texas Pattern notched guide shoe set '. Insert float set 864'. Cemented w/400 sacks Pacesetter Lite, 1/4#/sack loseal, 3% CaCl2. Tailed in w/300 sacks Class "C" 2% CaCl2. Compressive strength cement - 1250 psi in 12 hours. PD 4:15 PM 5-19-83. Bumped plug to 1000 psi, eased pressure and float held okay. Cement circulated 50 sacks. to pit. WOC. 11ed out 10:15 AM 5-20-83. WOC 18 hours. Nippled up and tested to 1000 psi for minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling. Subsurface Safety Valve: Manu. and Type Set @Ft. 18. Inereby certify that the foregoing is true and correct production signed Landard or LLAN with the foregoing is space for Federal or State office use) Date	MULTIPLE COMPLETE	
ROSWELL, NEW MEXICO 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work. ¹ including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work. ¹ inded 14-3/4" hole 7:15 AM 5-18-83. Set 40' of 20" conductor pipe. Ran 23 joints 10-3/4" 40.5# J-55 casing set 904'. 1-Texas Pattern notched guide shoe set i. Insert float set 864'. Cemented w/400 sacks Pacesetter Lite, 1/4#/sack cement - 1250 psi in 12 hours. PD 4:15 PM 5-19-83. Bumped plug to 1000 psi, leased pressure and float held okay. Cement circulated 50 sacks. to pit. WOC. illed out 10:15 AM 5-20-83. WOC 18 hours. Nippled up and tested to 1000 psi for minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling. Subsurface Safety Valve: Manu. and Type Set @	ROSWELL, NEW MEXICO 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical deptils for all markers and zones pertinent to this work.)* dded 14-3/4" hole 7:15 AM 5-18-83. Set 40' of 20" conductor pipe. Ran 23 joints 10-3/4" 40.5# J-55 casing set 904'. I-Texas Pattern notched guide shoe set '. Insert float set 864'. Cemented w/400 sacks Pacesetter Lite, 1/4#/sack loseal, 3% CaCl2. Tailed in w/300 sacks Class "C" 2% CaCl2. Compressive strength cement - 1250 psi in 12 hours. PD 4:15 PM 5-19-83. Bumped plug to 1000 psi, eased pressure and float held okay. Cement circulated 50 sacks. to pit. WOC. 11ed out 10:15 AM 5-20-83. WOC 18 hours. Nippled up and tested to 1000 psi for minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling. Subsurface Safety Valve: Manu. and Type Set @Ft. 18. Thereby certify that the foregoing is true and correct production signed Carlies of MAY' 3*1 1983 DATE		iAS
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Inded 14-3/4" hole 7:15 AM 5-18-83. Set 40' of 20" conductor pipe. Ran 23 joints 10-3/4" 40.5# J-55 casing set 904'. 1-Texas Pattern notched guide shoe set '. Insert float set 864'. Cemented w/400 sacks Pacesetter Lite, 1/4#/sack closeal, 3% CaCl2. Tailed in w/300 sacks Class "C" 2% CaCl2. Compressive strength cement - 1250 psi in 12 hours. PD 4:15 PM 5-19-83. Bumped plug to 1000 psi, leased pressure and float held okay. Cement circulated 50 sacks. to pit. WOC. illed out 10:15 AM 5-20-83. WOC 18 hours. Nippled up and tested to 1000 psi for minutes, 0K. Reduced hole to 7-7/8". Drilled plug and resumed drilling. Subsurface Safety Valve: Manu. and Type Set @Ft. 18. Thereby certify that the foregoing is true and correct Production Signed Construction of the production septement of the subsurface state of the subsurface for rederal or State office use) APPROVED BY (ORIG. SGD.) DAVID R. GLASS DATE	17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* dded 14-3/4" hole 7:15 AM 5-18-83. Set 40' of 20" conductor pipe. Ran 23 joints 10-3/4" 40.5# J-55 casing set 904'. 1-Texas Pattern notched guide shoe set '. Insert float set 864'. Cemented w/400 sacks Pacesetter Lite, 1/4#/sack loseal, 3% CaCl2. Tailed in w/300 sacks Class "C" 2% CaCl2. Compressive strength cement - 1250 psi in 12 hours. PD 4:15 PM 5-19-83. Bumped plug to 1000 psi, eased pressure and float held okay. Cement circulated 50 sacks. to pit. WOC. 11ed out 10:15 AM 5-20-83. WOC 18 hours. Nippled up and tested to 1000 psi for minutes, 0K. Reduced hole to 7-7/8". Drilled plug and resumed drilling. Subsurface Safety Valve: Manu. and Type		V MEXICO
Idded 14-3/4" hole 7:15 AM 5-18-83. Set 40' of 20" conductor pipe. Ran 23 joints 10-3/4" 40.5# J-55 casing set 904'. 1-Texas Pattern notched guide shoe set 4'. Insert float set 864'. Cemented w/400 sacks Pacesetter Lite, 1/4#/sack Iloseal, 3% CaCl2. Tailed in w/300 sacks Class "C" 2% CaCl2. Compressive strength cement - 1250 psi in 12 hours. PD 4:15 PM 5-19-83. Bumped plug to 1000 psi, leased pressure and float held okay. Cement circulated 50 sacks. to pit. WOC. illed out 10:15 AM 5-20-83. WOC 18 hours. Nippled up and tested to 1000 psi for minutes, 0K. Reduced hole to 7-7/8". Drilled plug and resumed drilling. Subsurface Safety Valve: Manu. and Type Is. I hereby certify that the foregoing is true and correct Production signep(dded 14-3/4" hole 7:15 AM 5-18-83. Set 40' of 20" conductor pipe. Ran 23 joints 10-3/4" 40.5# J-55 casing set 904'. 1-Texas Pattern notched guide shoe set '. Insert float set 864'. Cemented w/400 sacks Pacesetter Lite, 1/4#/sack loseal, 3% CaCl2. Tailed in w/300 sacks Class "C" 2% CaCl2. Compressive strength cement - 1250 psi in 12 hours. PD 4:15 PM 5-19-83. Bumped plug to 1000 psi, eased pressure and float held okay. Cement circulated 50 sacks. to pit. WOC. lled out 10:15 AM 5-20-83. WOC 18 hours. Nippled up and tested to 1000 psi for minutes, 0K. Reduced hole to 7-7/8". Drilled plug and resumed drilling. Subsurface Safety Valve: Manu. and Type Is I hereby certify that the foregoing is true and correct Production signed CEPTED FOR RECORD is space for Federal or State office use) APPROVED BY (ORIG. SGD.) DAVID R. CLASS conditions of APPROMENT of APPROMENTIONS of APPROVED Set (NEW MEXICO	17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	all pertinent details, and give pertinent dates, rectionally drilled, give subsurface locations and
18. I hereby certify that the foregoing is true and correct SIGNED	18. I hereby certify that the foregoing is true and correct SIGNED	10-3/4" 40.5# J-55 casing set 904'. 1-Texas Pat '. Insert float set 864'. Cemented w/400 sacks loseal, 3% CaCl2. Tailed in w/300 sacks Class " cement - 1250 psi in 12 hours. PD 4:15 PM 5-19- eased pressure and float held okay. Cement circ lled out 10:15 AM 5-20-83. WOC 18 hours. Nippl	tern notched guide shoe set Pacesetter Lite, 1/4#/sack C" 2% CaCl2. Compressive strength 83. Bumped plug to 1000 psi, ulated 50 sacks. to pit. WOC. ed up and tested to 1000 psi for
ACCEPTED FOR RECORD is space for Federal or State office use) APPROVED BY (ORIG. SGD.) DAVID R. GLASS CONDITIONS OF APPROMAYF 3NI 1983 ROSWELL, NEW MEXICO	ACCEPTED FOR RECORD is space for Federal or State office use) APPROVED BY (ORIG. SGD.) DAVID R. GLASS CONDITIONS OF APPROMAYES I 1983 ROSWELL, NEW MEXICO *See Instructions on Reverse Side	Subsurface Safety Valve: Manu. and Type	Set @ Ft.
ACCEPTED FOR RECORD is space for Federal or State office use) APPROVED BY (ORIG. SGD.) DAVID R. GLASS CONDITIONS OF APPROMAY'S NI 1983 ROSWELL, NEW MEXICO	ACCEPTED FOR RECORD is space for Federal or State office use) APPROVED BY (ORIG. SGD.) DAVID R. GLASS CONDITIONS OF APPROMAYES 11983 ROSWELL, NEW MEXICO *See Instructions on Reverse Side	18. I hereby certify that the foregoing is true and correct Production	
ACCEPTED FOR RECORD is space for Federal or State office use) APPROVED BY (ORIG. SGD.) DAVID R. GLAESS CONDITIONS OF APPROMAYES 1983 ROSWELL, NEW MEXICO	ACCEPTED FOR RECORD is space for Federal or State office use) APPROVED BY (ORIG. SGD.) DAVID R. GLASS CONDITIONS OF APPROMAYES 1983 ROSWELL, NEW MEXICO *See Instructions on Reverse Side	signed <u>and</u> <u>or allell</u> title <u>Supervisor</u>	DATE5-23-83
APPROVED BY (ORIG. SGD.) DAVID R. GLASS DATE DATE DATE DATE NONDITIONS OF APPROMAY 3"1 1983	APPROVED BY (ORIG. SGD.) DAVID R. GLASS CONDITIONS OF APPROMAY SNI 1983 ROSWELL, NEW MEXICO *See Instructions on Reverse Side	ACCEPTED FOR RFCORD is space for Federal or State of	fice use)
	•See Instructions on Reverse Side	APPROVED BY (ORIG. SGD.) DAVID R. GLASS	
		MAY 3 1 1983	