

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen a well back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐ OCT 5 1982

2. NAME OF OPERATOR
Yates Petroleum Corporation, C. D.

3. ADDRESS OF OPERATOR
ARTESIA, OFFICE
207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660 FNL & 990 FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:
TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT

RECEIVED

AUG 26 1982

OIL & GAS
MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO

5. LEASE
NM 18822
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Leeman OC Federal
9. WELL NO.
4
10. FIELD OR WILDCAT NAME
Pecos Slope Abo
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit D, Sec. 20-T7S-R26E
12. COUNTY OR PARISH
Chaves
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3577' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 14-3/4" hole at 10:00 AM 8-18-82. Set 50' of 20" conductor pipe. Ran 23 joints of 10-3/4" 40.5# J-55 casing set at 895'. 1-Texas Pattern notched guide shoe at 895'. Regular insert float at 855'. Cemented w/400 sacks Pacesetter Lite, 3% CaCl₂, 1/4#/sack celloseal. Tailed in w/300 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hrs. PD 11:30 PM 8-19-82. Bumped plug to 800 psi, released pressure and float held okay. Cement circulated 50 sacks to pit. Drilled out at 5:30 PM 8-20-82. WOC 18 hrs. Nipped up and tested to 1000#, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *J. A. L. L. L.* TITLE Engineering Secty DATE 8-24-82

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

OCT 4 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side