

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

NM OIL CONS. CORP.  
Drawer DD  
Artesia, NM 88210

Form Approved.  
Budget Bureau No. 42-R1424

C19F

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen a well into a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

OCT 18 1982

2. NAME OF OPERATOR

MESA PETROLEUM CO.

3. ADDRESS OF OPERATOR

O. C. D.  
ARTESIA, OFFICE

1000 VAUGHN BUILDING/MIDLAND TX 79701-4493

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

1650' FNL & 784' FWL

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: SAME

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) TD, 4 1/2 csg & cmt ☐

5. LEASE  
NM-36648

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
CHINA FEDERAL

9. WELL NO.  
9

10. FIELD OR WILDCAT NAME  
UNDESIGNATED ABO

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC 20, T7S, R23E

12. COUNTY OR PARISH  
CHAVES

13. STATE  
NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
4054' GR

(NOTE: Report results of multiple completion or logs change on Form 9-330.)

RECEIVED  
JUL 1 1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 7 7/8" hole on air to 2080' -- hit water at 12 to 14 BPH. Switched to mud at 2550' and drilled to TD of 3110' on 6-25-82. Ran 87 jts, 11.6#, N-80 and 8 jts 13.5#, N-80, 4 1/2" casing set at 3053'. Cemented w/350 sxs Class "C" + 5#/sx KCL + 3/10% Halad-4 + 2/10% CFR-2. PD at 2:30 PM, 6-28-82. Cement did not circulate. Released rig at 6:00 PM, 6-28-82. WOCU.

XC: MMS (7), TLS, CEN RCDS, ACCTG, MEC, ROSWELL, REM, FILE, (PARTNERS )

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct. REGULATORY COORDINATOR 6-29-82

SIGNED R.F. MacA TITLE \_\_\_\_\_ DATE \_\_\_\_\_

APPROVED BY (ORIG. SGD.) DAVID R. GLASS DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

OCT 15 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO