

Dec. 1973

Drawer 00

Artesia, NM 88210

Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐ JUL 1 1982
2. NAME OF OPERATOR MESA PETROLEUM CO. ✓
3. ADDRESS OF OPERATOR O. C. D. ARTESIA, OFFICE
1000 VAUGHN BUILDING/MIDLAND TX 79701-4493
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 660' FNL & 2310' FEL
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: SAME

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐ ☐
FRACTURE TREAT ☐ ☐
SHOOT OR ACIDIZE ☐ ☐
REPAIR WELL ☐ ☐
PULL OR ALTER CASING ☐ ☐
MULTIPLE COMPLETE ☐ ☐
CHANGE ZONES ☐ ☐
ABANDON* ☐ ☐
(other) Spud, 8 5/8" csg & cmt

5. LEASE NM-36648

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
CHINA FEDERAL

9. WELL NO.
11

10. FIELD OR WILDCAT NAME
UNDESIGNATED ABO

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC 20, T7S, R23E

12. COUNTY OR PARISH CHAVES 13. STATE NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4009' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well with 12 1/4" hole on 6-12-82. Drilled with air to 1451' and ran 37 jts 8 5/8", 24#, K-55 casing set at 1451'. Cemented with 700 sxs Thixalite + 4% CaCl + 1/4#/sx flocele and tailed in with 200 sxs Class "C" + 2% CaCl. PD at 2:00 PM, 6-13-82. Cement did not circulate. Ran temperature survey --- TOC at 540'. Set four plugs with a total of 700 sxs Thixset + 4% CaCl to circulate cement. Tested BOP's and casing to 600 psi for 30 mins -- OK. Reduced hole to 7 7/8" and drilled ahead on 6-14-82. WOC total of 23 1/2 hrs.

XC: MMS (7), TLS, CEN RCDS, ACCTG, MEC, ROSWELL, REM, FILE, (PARTNERS)

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct. REGULATORY COORDINATOR 6-16-82

SIGNED R. E. Nathan TITLE _____ DATE _____

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUN 30 1982
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

RECEIVED
JUN 18 1982
OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO