ೆ ಬೆಂ

NEW MEXICO

9

UN .D STATES Drawer DD

DEPARTMENT OF THE INTERIOR, NM 88210 **GEOLOGICAL SURVEY**

5.	LEASE
	NM-36648

		2000
6.	IF INDIAN, ALLOTTEE OR TRIBE	NAMÉ

SUNDRY	NOTICES	AND	REPORTS ON WELLS	
not use this to		A	NECENTAL .	

(Do not use this form for proposals to drill or to deepen or plug back to different reservoir. Use Form 9–331–C for such proposals.)

1.	oil well		gas well		other	JUN 3 0 1982	
2.	NAME	OF	OPERAT	FOR		O. C. D.	
	MES	A P	ETROLE	LUM	co. V	ABTES:	

ARTESIA, OFFICE 3. ADDRESS OF OPERATOR

1000 VAUGHN BUILDING/MIDLAND TX 79701-4493

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 1980' FNL & 500' FWL

AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH:

SAME

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

12 10. FIELD OR WILDCAT NAME 4 UNDESIGNATED ABO

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME CHINA FEDERAL

11. SEC., T., R., M., OR BLK. AND SURVEY OR ARFA

SEC 19, T7S, R23E 12. COUNTY OR PARISH 13. STATE

14. API NO.

CHAVES

9. WELL NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD) 3983' GR

(NOTE: Report results of multiple completion or zone

change on Form 9-330.)

REQUEST FOR APPROVAL TO: **TEST WATER SHUT-OFF** FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING

MULTIPLE COMPLETE **CHANGE ZONES** ABANDON* (other) Spud, 8 5/8" csg & cmt

SUBSEQUENT REPORT OF:

OIL & GAS HIS, GEOLOGICAL SURVEY

OSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well with 12%" hole on 6-18-82. Drilled on air to 1502 and gan 35 jts 8 5/8", 24#, K-55 casing set at 1502'. Cemented with 700 sxs Thixalite + 1/1/sx flocele + 4% CaCl and tailed in with 200 sxs Class "C" + 2% CaCl. PD at 5:00 PM, 6-19-82. Cement did not circulate. Set four plugs with a total of 800 stage Thixset + 4% CaCl to circulate cement. Tested BOP's and casing to 600 psi for 30 mins -- OK. Reduced hole to 7 7/8" and drilled ahead on 6-20-82. WOC total of 25 hours.

MMS (7), TLS, CEN RCDS, ACCTG, MEC, ROSWELL, REM, FILE, (PARTNERS

18. I hereby certify that the foregoing is true and correct REGULATORY COORDINATOR

6-21-82

Set @

TITLE (This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

Subsurface Safety Valve: Manu. and Type _

ACCEPTED FOR RECORD

U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXIC

*See Instructions on Reverse Side

NSL 1548