

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐  
2. NAME OF OPERATOR  
McClellan Oil Corporation  
3. ADDRESS OF OPERATOR  
P.O. Drawer 730, Roswell, NM 88201  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FNL & 660' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) Casing and Cement		

5. LEASE  
NM-16109  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME RECEIVED  
8. FARM OR LEASE NAME  
HM Federal OCT 18 1982  
9. WELL NO.  
1 O.C.D.  
10. FIELD OR WILDCAT NAME  
Wildcat - SH  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 7-T12S-R29E  
12. COUNTY OR PARISH 13. STATE  
Chaves New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3769 G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

7/20/82 Move in Comanche Rig #1. Spud with 15" bit.

7/27/82 TD at 406: Ran 406' of 12-3/4" casing. Cemented with 206 sacks Class "C" with 2% CaCl<sub>2</sub>. Ready-mixed to surface with 5 yards. WOC 18 hours.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_ TITLE Operations Manager DATE July 28, 1982

ACCEPTED FOR RECORD  
(ORIG. CSD.) DAVID R. GLASS  
(This space for Federal or State office use)  
APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL IN ANY \_\_\_\_\_  
OCT 15 1982  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO  
See Instructions on Reverse Side

RECEIVED  
JUL 29 1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO