

C/SF

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a new reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐ P&A
2. NAME OF OPERATOR  
Yates Petroleum Corporation ✓
3. ADDRESS OF OPERATOR  
207 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980 FNL, 1650 FWL, Sec. 12-9S-24E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input checked="" type="checkbox"/>	<input type="checkbox"/>

(other) \_\_\_\_\_

5. LEASE  
NM 16070
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Fleming UF Federal
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
Und. Abo
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Unit F, Sec. 12-T9S-R24E
12. COUNTY OR PARISH  
Chaves
13. STATE  
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3560' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

This well was drilled to a total depth of 4041'. Propose to plug with cement plugs as follows:

3312-3412' (Abo top @3362')  
1172-1272' (Glorieta top @1222')  
800-900' (10-3/4" casing set @ 856' w/cement circulated)  
25 sack plug at surface

Verbal approval for the above program given by Mr. James Gillham, MMS, Roswell, on 7-4-82.

Regulation abandonment marker will be installed and surface restoration will be in accordance with MMS-BLM requirements.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED James A. Gillham TITLE Engineering Secty DATE 7-6-82

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_

APPROVED  
JUL 9 1982  
JAMES A. GILLHAM  
DISTRICT SUPERVISOR

\*See Instructions on Reverse Side

RECEIVED  
JUL 8 1982

U.S. GEOLOGICAL SURVEY  
NEW MEXICO