Form 9–331	NM OIL CONS. COMMIS Drawer DD Artesia, NM 88210	Form Approved. Budget Bureau No. 42-R1424	ten.
Dec. 1973 UNITED STATES DEPARTMENT OF THE INTE GEOLOGICAL SURVEY	ES	5. LEASE NM 22614	Ŧ
		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REF (Do not use this form for proposals to drill or to d	PORTS PENEEULS	7. UNIT AGREEMENT NAME	
reservoir. Use Form 9-331-C for such proposals.)	flin	8. FARM OR LEASE NAME	فيطلب م
1. oil gas 🕥	- JUN 1 1982	Mike Harvey TR Federal	-
well well to other	O.C.D	9. WELL NO.	
2. NAME OF OPERATOR			
Yates Petroleum Corporat	ARTESIA, OFFICE	10. FIELD OR WILDCAT NAME Pecos Slope Abo	
3. ADDRESS OF OPERATOR			
207 South 4th St., Artes	sia, NM 88210	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
4. LOCATION OF WELL (REPORT LOCATI	ION CLEARLY. See space 17	Unit I, Sec. 3-T5S-R24E	
below.) 1980 FSL & 660 FEL	, Sec. 3-5S-24⊠	12. COUNTY OR PARISH 13. STATE	1000
AT SURFACE: AT TOP PROD. INTERVAL:		Chaves NM	1000 ····
AT TOTAL DEPTH:		14. API NO.	
16. CHECK APPROPRIATE BOX TO INDI	CATE NATURE OF NOTICE,		r
REPORT, OR OTHER DATA		15. ELEVATIONS (SHOW DF, KDB, AND WD) 3959.2' GR	•
REQUEST FOR APPROVAL TO: SU	BSEQUENT REPORT OF:		
TEST WATER SHUT-OFF	X	NET EN	
FRACTURE TREAT		1316月科区业均111	
SHOOT OR ACIDIZE		(NOTE: Report results of multiple completion or zone	ji majira
REPAIR WELL		IAY 2018 1982 rm 9-110)	
PULL OR ALTER CASING		A HIAT A CIJUL LI	
CHANGE ZONES			5
ABANDON*		HIS DEDLOGICAL SURVEY	¥
(other)		NOSWELL NEW MEXICO	

measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 14-3/4" hole 11:00 AM 5-13-82. Set 40' of 20" conductor pipe. Ran 22 joints of 10-3/4" 40.5# ST&C casing set 883'. 1-Texas Pattern guide shoe at 883'. Insert float 842'. Cemented w/500 sacks Halliburton Lite, 1/4#/sack flocele and 2% CaCl₂. Tailed in w/200 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1365 psi in 12 hours. PD 7:05 PM 5-14-82. Bumped plug to 500 psi, released pressure and float held okay. Cemented circulated 25 sacks. WOC. Drilled out 1:05 PM 5-15-82. Nippled up and tested to 1000 psi, okay. Reduced hole to 9-7/8". Drilled plug and resumed drilling.

1

filled plug and resume	d driffing.	ACCEPTED FOR RECORD	
		ACCEPTED	1
		MAY 2 7 1982	
Subsurface Safety Valve: Man	u. and Type	Set @URVE	〈 \ Ft. > \
18. Thereby certify that the fo	pregoing is true and correct	MAY 2 1 ISU Set @URVE U.S. GEOLOGICAL NEW MEXICO NEW MEXICO State office use) DATE	
SIGNED Ly lend and	Lo delle Inte Engineers	ng Secty Rate 5-21-02	
$\overline{\mathcal{V}}$	(This space for Federal or	State office use)	
APPROVED BY	TITLE	DATE	

CONDITIONS OF APPROVAL, IF ANY

*See Instructions on Reverse Side

× . .