

C/SF

UNITED STATES Artesia, NM 88210
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to develop a well back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other SEP 29 1982

2. NAME OF OPERATOR

MESA PETROLEUM CO.O. C. D.3. ADDRESS OF OPERATOR ARTESIA, OFFICE1000 VAUGHN BUILDING/MIDLAND TX 79701-44934. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 990' FNL & 890' FEL NE 1/4 NE 1/4 A

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: SAME

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) SPUD, 8 5/8" CSG & CMT'D

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well with 12 1/4" hole on 7-8-82. Lost circulation on air at 253' and then hole fell in at 332'. Set 900 sx "C" + 1/4# Flocele + 4% CaCl to condition hole. Drilled to 1436' and attempted to run casing. Hit bridge at 312' and at 482'. Reamed hole and pumped 650 sx Thixset + 4% CaCl + 1/4#/sx Flocele. Drilled cement and ran 33 jts 8 5/8", 24#, K-55 casing set at 1394'. Cemented with 700 sx Thixset + 1/4#/sx Flocele + 4% CaCl and tailed in with 200 sx "C" + 2% CaCl. PD @ 2 AM 7-12-82. Cement did not circulate. Ran temp survey --- TOC @ 610'. Set six plugs with a total of 565 sx Thixset + 4% CaCl to circulate cement. Tested BOPs and casing to 600 psi for 30 mins -- OK. Reduced hole to 7 7/8" and drilled ahead on 7-13-82. WOC total of 28 hours.

XC: MMS (7), TLS, CEN RCDS, ACCTG, MEC, ROSWELL, REM, FILE, (PARTNERS)
Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

R. E. MookTITLE REGULATORY COORDINATORDATE 6-25-82

(This space for Federal or State office use)

ACCEPTED FOR RECORD
APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:SEP 27 1982U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO