

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐ **OIL & GAS**
2. NAME OF OPERATOR **BERGE EXPLORATION, INC.**
3. ADDRESS OF OPERATOR **7100 N. BROADWAY, STE. 2-L, DENVER, CO 80221**
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: **1980' FSL 660' FEL**
AT TOP PROD. INTERVAL: **Same**
AT TOTAL DEPTH: **Same**

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) <u>set production casing</u>		

5. LEASE **LC-067811-A**
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME **RECEIVED**
8. FARM OR LEASE NAME **Dale Federal**
9. WELL NO. **#17**
10. FIELD OR WILDCAT NAME **Granite Wildcat**
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA **Sec. 26, T7S, R26E**
12. COUNTY OR PARISH **Chaves**
13. STATE **New Mexico**
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD) **3841' GL 3853' KB**

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 7-7/8" hole @ 6301' @ 4:00 a.m. 10/9/82. Ran 170 jts. 4 1/2" 10.50 K 55 ST&C casing @ approx. 6290' w/FC @ 6250' and cement basket @ 2130'. Cemented w/400 sx Halliburton-Lite + 6 sx salt + 1/4#/sx Flocele, tailed w/600 sx class "C" + 50/50 poz + 2% gel + 2/10 of 1% CFR-2 + 3/10 of 1% Halad-4 to approx. 3600'. Plug down @ 2:00 a.m. 10/11/82. Cemented 1" Stage I w/200 sx Halliburton-Lite to approx. 1300'. Cemented 1" Stage II w/200 sx Halliburton-Lite to approx. 810'. Completed @ 6:35 a.m. 10/11/82.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ally L. Morris TITLE Geologist DATE 10/18/82

APPROVED BY _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: **OCT 20 1982**

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO *See Instructions on Reverse Side