

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Berge Exploration, Inc. ✓

DEC 22 1982

3. ADDRESS OF OPERATOR
O. C. D.
7100 N. Broadway, Ste. 2L, Denver, CO 80221

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL, 660' FEL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☒
☒
☐
☐
☐
☐
☐
☐
☐

RECEIVED
DEC 20 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS

MINERALS MGMT. SERVICE

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/11/82 WIH w/3 7/8" bit, DOC to 6270' PBTD.
11/14/82 Perfed L/Montoya w/1 JSPF @ 6240, 41, 42, 45, 46, 50, 51, 52;
0.38" diameter (8 holes total).
11/15/82 Set pkr @ 6170'. Acidize L/Montoya w/38 bbls 15% HCl-NE-FE.
11/16/82 Swbd 50 bbls wtr, tr oil, no gas.
11/17/82 Set CIBP @ 6230', perfed U/Montoya w 1 JSPF @ 6164'-6172';
0.38" diameter (9 holes total).
11/19/82 Acidize U/Montoya @ 6164'-6172' w/43 bbls 15% HCl-NE-FE, made good
amt of gas w/wtr and tr oil.
11/20/82 Swbd 20 BWPB w/some gas, no oil.
11/21/82 Set CIBP @ 6150', perfed Abo @ 4715'-4727' w/1 JSPF; 0.38" diameter
(13 holes total)
11/22/82 Set pkr @ 4600', treated w/1100 gals 7½% HCl-NE-FE

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.
11/23/82 Sand frac Abo @ 4715'-4727' w/16,100 gals gelled fluid + 6900 gals CO2
18. I hereby certify that the foregoing is true and correct + 28,000# 20/40 mesh sand, SI 1½ hrs. Begin testing.

SIGNED Elissa J. Roselyn TITLE Geologist DATE 12/16/82

ACCEPTED FOR RECORD

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY _____
CONDITIONS OF APPROVAL _____
DEC 21 1982

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.