NN OIL_CONS. CUMIDDION Dec. 1973 Draw: DD ArteMATEDMSTREES DEPARTMENT OF THE INTERIOR	Budget Bureau No. 42-R1424 5. LEASE NM-36644	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to dill or to deepen or plug back to a different eservoir. Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME	
eservoir. Use Form 9-331-C for such praposals.)	8. EARM OR LEASE NAME DEBBIE FEDERAL	
1. oil well       gas well well other         2. NAME OF OPERATOR       SEP 2 9 1982	9. WELL NO.	
MESA PETROLEUM CO.V	10 NELED OR WILDCAL NAME	
3. ADDRESS OF OPERATOR O. C. D. 1000 VAUGHN BUILDING/MIDLANDESTA, Z9701-4493	11. SEC., T., R., M., OR BLK. AND SURVEY OR	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 850' FNL & 850' FWL	AREA SEC 29, T7S, R23E	
AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: SAME	12. COUNTY OR PARISH 13. STATE CHAVES NEW MEXICO	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 4028 GR	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	L	
TEST WATER SHUT-OFF		
PULL OR ALTER CASING  MULTIPLE COMPLETE CHANGE ZONES	(NOTE: Report results of multiple completion or zone change on Form 9–330.)	
ABANDON* (other)		

1.1.4

୍ଟଙ୍କ

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded well with  $12\frac{1}{4}$ " hole on 7-17-82. Drilled to 1393' and ran 31 jts 8 5/8", 24#, K-55 casing set at 1390'. Cemented with 700 sxs Thixalite +  $\frac{1}{4}$ #/sx flocele + 4% CaCl and tailed in with 200 sxs Class "C" + 2% CaCl. PD at 6:00 AM, 7-21-82. Cement did not circulate. Ran temperature survey --- TOC at 580'. Set six plugs with a total of 640 sxs Class "C" + 4% CaCl and 95 buckets of gravel to circulate cement. Tested BOP's and casing to 600 psi for 30 mins -- OK. Reduced hole to 7 7/8" and drilled ahead on 7-22-82. WOC total of  $26\frac{1}{2}$  hours.

XC: MMS (7), TLS, CEN RCDS, A Subsurface Safety Valve: Manu. and Type		
18. I hereby certify that the foregoing is true SIGNED	and correct REGULATORY COORDINATO	R 7-23-82
(1	This space for Federal or State office use)	
APPROVED BACCEPTED FOR RECORD CONDITIONS OF APPROVAL IF ANY: SEP 2 1992	TITLE	DATE
	*See Instructions on Reverse Side	
U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO		
. · · ·		