

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Wallace Oil & Gas</u>		Lease <u>HAHN</u>		Well # <u>1</u>	
Location of Well	Unit <u>5</u>	Section <u>19</u>	Township <u>11 S</u>	Range <u>24 E</u>	County <u>CHAVES</u>
Drilling Contractor	<u>TEX-MEX. DRILLING CO.</u>		Type of Equipment <u>ROTARY</u>		

* WITNESS

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>15 1/4"</u>	<u>13 3/8"</u>	<u>48#</u>		<u>450</u>	<u>420</u>
* <u>12 1/4"</u>	<u>8 5/8"</u>	<u>24#</u>		<u>1200</u>	<u>circ. 750</u>
<u>7 7/8"</u>	<u>4 1/2"</u>	<u>10.5#</u>		<u>4500</u>	<u>250</u>

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected)

Inspected by _____ date _____

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 885 sxs

Type of Shoe used Guide Float collar used Insert Btm 3 jts welded Yes

TD of hole 1275' Set 1253' Feet of 8 5/8 Inch 24 # Grade J-55

New used csq. @ 1253' with 200 sacks neat cement around shoe 2% CaCl₂
+ 300 sack Pacesetter l/t additives cl.c w/ 1/4" permack., 10# Gilsomite, 2% CaCl₂

Plug down @ 11:59 (AM) (PM) Date 9/19/82

Cement circulated NO No. of Sacks AFTER 1" 10 sxs

Cemented by Western Witnessed by Larry Brooks

Temp. Survey ran @ 6:00 (AM) (PM) Date 9/19/82 Top cement @ 190'

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: Tex. pattern shoe

Landing jt. 1285'

Tagged @ 193' w/ 1"

Pumped 85 sx. cl.c. neat. circ 10 sxs. to the pit.

By Log: 1325' of csq. (LB)