STATE OF NEV						
ENERGY AND MINERA		NI CONCEDVA	TION DIVIGIA			
69. 97 (D*111 \$100			TION DIVISION		farm C-103 ·	
SANTA FE		P. O. BO	K (7 & 1) Y 3.12		ierrsed 10-1-78	
FILE		SANTA FE, NEW	MEXICO 87501	<u></u>		
U.S.G.S.			OOT 50 1002	5a. Indicate T		
LAND OFFICE			OCT 2 4 1982	State	Fee XX	
OPERATOR	<u></u>		O. C. D.	5, State Off &	Gas Lease No.	
					mmmmmm	
IDE NOT USE THE	TON YNDRUE	TICES AND REPORTS ON TO BRILL ON TO BEILD ON TO BEILD ON TO BEILD ON TO BEILD ON THE BEILD OF THE STATE OF THE BEILD OF TH	HELLSMIESIA DEFICE			
1.	USE "APP. ICATION FOR	PERMIT -" (FORM C-1011 FOR 5.	- PRCFOSALS.)	7. Unit Agree	cent year	
011	WELL XX OTH			, em ngreer		
, liame of Operator	WILL AA' OTH	4ER+		8. Form or Le	use licre	
					1 n	
Wallace Oil & Gas, Inc. L Address of Gregator 50 Penn Place, Suite 850, Okla. City, OK 73118					111	
1. Location of Well	ce, Suite 850,	Okla. City, OK /31	.18	10. Field and	Poor, at visideat	
-	T 1000	FEET FROM THE BEST	1000	W	ildcat 💯 🥳	
UNIT LETTER	J190U	FEET FROM THE LEGST	LINE AND FE	ET CROM CTTTTT		
Courth		19 TOWNSHIP 11S	27.5			
THE -BOULTE	UNC. SCCTION	15 TOWNSHIP 115	RANGEZ4E	- nmon: (///////		
THITTITTE:	TTTTTTTT	15. Elevation (Show whether	F. RT, GR, etc.)	12. County	4444	
		Gr. 3652'		Chaves		
777777777777777777777777777777777777777	Chack Appea	priate Box To Indicate N	sture of Notice Peport			
NC	CHECK Applo	•	•	OF OTHER DATA QUENT REPORT O	F.	
140	71102 01 1111 E.T.		30832	QUENT KETOKTO		
PERFORM REMEDIAL WORL		PLUG AND ABANDON	FEMEDIAL WORK		TERING CASING	
TEMPORARILY ABANDON			COMMENCE DRILLING OPHS.	Ħ	G AND ABANDONMENT	
PULL OR ALTER CASING		CHANGE PLANS	CASING TEST AND CEMENT JOB	x	_	
		_	OTHER			
OTHER						
		s (Clearly state all pertinent des		-luding antiquend data		
work) SEE RULE 11		s (Clearly state all pertinent de	, and give pertinent dates, tr	ictualing estimated date	of startify any proposed	
0.100.100						
	9/20/82 Commence Drilling operations.					
	9/27/82 Reached Total depth at 4100'. 9/29/82 Finished logging. Plugged back to Intermediate, set plug.					
9/29/82	t plug,	01001				
		Spotted 25 sxs of cement from 4,080' to 3,980'; 25 sxs from 3280' to 3180'; 25 sxs from 1300' to 1200'.				
	23 SES Irom	1300 60 1200 .				
	Released rig at 9:00 P.M.					
	Referenced Fig at 5.00 f.m.					
	WOCT					
		is true and complete to the best :	/ b			
is. I hereby certify that	ine near ition above i	a true and complete to the best of	. inv anowiedle and bellet.			
1/2/-		1/8//		•	0/10/00	
SIGNED 15/2000/SCE	<u> </u>	TITLE PT	oduction Secretary	DATE	.0/19/82	
	1 h/M.		DIL AND GAS INSPECTOR	N()V 3 1982	