PULL OR ALTER CASING MULTIPLE COMPLETE **CHANGE ZONES** ABANDON\*

(othe@pud, 10 3/4"

BOOK HATTER D

CSg

Form Approved. Budget Bureau No. 42-R1424

change on Form 9-330.)

ROSWELL, NEW MEXICO

5. LEASE

Artes UNITED STATES

DEPARTMENT OF THE INTERIOR  GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deeper (or dry France).	7. UNIT AGREEMENT NAME			
(Do not use this form for proposals to drill or to deeper of the Garage of the contract of the	8. FARM OR LEASE NAME			
1. oil gas	LEILA FEDERAL			
well well well well well well other OCT 5 1982	9. WELL NO.			
2. NAME OF OPERATOR	2			
MESA PETROLEUM CO. V. O. C. D.	10. FIELD OR WILDCAT NAME			
3. ADDRESS OF OPERATOR ARTESIA, OFFICE	WILDCAT ABO			
1000 VAUGHN BUILDING/MIDLAND TX 79701-4493 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA			
S. January	SEC 24, T6S, R26E			
AT SURFACE: 1980' FSL & 1980' FEL	12. COUNTY OR PARISH 13. STATE			
AT TOP PROD. INTERVAL:	CHAVES NEW MEXICO			
AT TOTAL DEPTH: SAME	14. API NO.			
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,				
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)			
	3817' GR			
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:				
TEST WATER SHUT-OFF				
REPAIR WELL	(NOTE: Report results of multiple completion or zone			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded well with 14 3/4" hole on 7-30-82. Drilled with mud to 978' and ran 23 jts 10 3/4", 40.5#, K-55 casing set at 978'. Cemented with 700 sxs Thixalite + 4% CaCl + 1/4 /sx flocele and tailed in with 200 sxs Class "C" + 2% CaCl. PD at 1:00 PM, 8-1-82. Circulated 50 sxs. Tested BOP's and casing to 600 psi for 30 mins -- OK. Reduced hole to 7 7/8" and drilled ahead on 8-3-82. Hit brackish water estimated at 5 BPH at 1315' increasing to 200 BPH at 1931 WOC total of 18½ hours.

				, ROSWELL,	REM, FI	LE, (PARTNERS	-	)
Subsurface	Safety Valve: M	lanu. and Type _				Set @	4 7 4 2	_ Ft.
18. I hereb	y certify that th	e foregoing is tru	e and correct			28	# 55 g	
SIGNED	REN	land	TITLE	TORY COORD	INATOR	8-4-82		
	ACCEP	TED FOR PECO	Phis space for Fe	deral or State office	ce use)			
APPROVED I		A.E.	TITLE		DATE		5/1/177	
CONDITIONS	OC OC						<u> </u>	3
	U.S. GEO	LOGICAL SUI	RVEY			AUG AUG	6 1982	
	ROSWEL	L, NEW MEX	CO Instructi	ons on Reverse S	ide		L& GAS Ochcal sit	8V#Y