

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
well well

2. NAME OF OPERATOR

Stevens Operating Corporation

3. ADDRESS OF OPERATOR

P. O. Box 2408, Roswell, New Mexico 88201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 330' FNL, 2310' FEL, Sec. 23, 7S, 26E

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Commencement, casing, treatment

5. LEASE

NM 27634

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME RECEIVED

8. FARM OR LEASE NAME

Hanagan Federal OCT 15 1982

9. WELL NO.

3

O. C. D.

10. FIELD OR WILDCAT NAME ARTESIA, OFFICE

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 23, T-7-S, R-26-E

12. COUNTY OR PARISH 13. STATE

Chaves

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3803 GR

RECEIVED

NOTE: Report results of multiple completion or zone change on Form 9-330.

AUG 12 1982

OIL & GAS

MINERALS MGMT. SERVICE

ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

7-25-82 Artesia Fishing Tool spud w/12 1/4" bit. Ran 8 5/8" 36# csg., set and cement at 302' w/200 sxs Class C, 2% S-1. Circ 24 sxs. Pressure up 1000# for 30 minutes logging no pressure decrease.

7-29-82 Ran 41 jts 4 1/2" 10.5# csg. Set and cement at 1630' w/200 sxs Self Stress, 2% CaCl<sub>2</sub>. Pressure up 1000# for 30 minutes logging no pressure decrease.

8-3-82 Perforated at 1450.5, 51, 51.5, 54.5, 55, 55.5, 56, 56.5, 60.5, 61, 61.5, 67.5, 68, 68.5, 70.5, 71, 74, 74.5, 75.

8-4-82 Ran 46 joints 2 3/8" tubing. Acidize w/8000 gals 28% HCL.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED David R. Thompson TITLE Prod. Coordinator DATE 8-9-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

(ORIG. CDC) DAVID R. GLASS

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

DATE \_\_\_\_\_

OCT 14 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side