Property of American	1.40	•.:
** ** (**!!* *!!!***		1
POISTRIBUTION		
SANTA FE		
FILE		
U.\$.Q.S.		
LAND OFFICE		
0.000	-	

DISTRIBUTION SANTA FE			
		7. O. BOX 2088	Form C-100 Revised 10
FILE	5,	ANTA FE, NEW MEXICO 87501	
U.8.0.6.	95D	7.1992	5a. Indicate Type of Lease
LAND OFFICE		· · · · · · · · · · · · · · · · · · ·	State Fee
OPERATOR		e de la companya del companya de la companya del companya de la co	5. State Oil & Gas Lease No.
<u> </u>	 ;	A P	
	<u> </u>		- Ammmmm
OG HOT PER THIS FORM F	INDRY NOTICES AN	ND REPORTS ON WELLS	
USC "API	CICATION FOR PERMIT -"	TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. IFORM C-1011 FOR SUCH PROPOSALS.	
011	٦		7. Unit Agreement Name
werr X	OTHER-		
me of Operator			f. Farm or Lease Name
MESA PETROLEUM C	0.		ERMA
dress of Operator			9. Well No.
1000 VAUGHN BUIL	DING/MIDLAND. T	TX 79701-4493	
Cation of Well		7,7,01 44,55	1
	660	COUMI	10. Field and Pool, or Wildcat
	000	OM THE SOUTH LINE AND 660	WILDCAT ABO
WEST	1	10S 24E	
		TOWNSHIP RANGE	- MMbr ()
177777777777777777777777777777777777777	THE THE PERSON OF THE PERSON O	vation (Show whether DF, RT, GR, etc.)	
	///////////////////////////////////////	3559' GR	12. County
	77777777	JJJJ GK	CHAVES
Che	ck Appropriate Bo	x To Indicate Nature of Notice, Report	or Other Data
NOTICE	F INTENTION TO:		QUENT REPORT OF:
		30832	QUENT REPORT OF:
DAM REMEDIAL WORK		<u></u>	 -
<u> </u>	٩٤	UG AND ABANDON REMEDIAL WORK	ALTERING CASING
DRARILY ABANDON		COMMENCE DRILLING OPHS.	PLUG AND ABAHOOHMEN
OR ALTER CABING	-	1 11	
	C H	ANGE PLANS CASING TEST AND CEMENT JOB	_**
	C H.		_A
nta	C H.	OTHER	
acribe Proposed or Complet			
Spudded well with 40.5#, K-55, ST&C CaCl and tailed 100 sxs to surface	n 14 3/4" hole C csg set at 94 In with 200 sxs	OTHER	ran 23 jts 10 3/4", 1/4#/sx flocele + 4% 0 AM, 9-1-82. Circ
Spudded well with 40.5#, K-55, ST&C CaCl and tailed 100 sxs to surface hole to 9 7/8" ar	n 14 3/4" hole C csg set at 94 in with 200 sxs ce. Tested BOP and drilled ahea	on 8-31-82. Drilled to 946' and 6'. Cemented with 700 sxs HLW + Class "C" + 2% CaCl. PD at 6:0's and casing to 600 psi for 30 d on 9-2-82. WOC total of 18 hor	ran 23 jts 10 3/4", 1/4#/sx flocele + 4% 0 AM, 9-1-82. Circ mins OK. Reduced urs.
Spudded well with 40.5#, K-55, ST&C CaCl and tailed 100 sxs to surface hole to 9 7/8" ar	n 14 3/4" hole C csg set at 94 in with 200 sxs ce. Tested BOP and drilled ahea	on 8-31-82. Drilled to 946' and 6'. Cemented with 700 sxs HLW + Class "C" + 2% CaCl. PD at 6:00's and casing to 600 psi for 30 d on 9-2-82. WOC total of 18 hor	ran 23 jts 10 3/4", ½#/sx flocele + 4% O AM, 9-1-82. Circ mins OK. Reduced urs.

COND TIONS OF APPROVAL, IF ANYL