

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

RECEIVED

SEP 16 1982

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
ARTESIAN ☒ Fee ☐

5. State Oil & Gas Lease No.
LG 6492

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Mesa Petroleum Company	8. Farm or Lease Name Panther State
3. Address of Operator P. O. Box 2009 / Amarillo, Texas 79189	9. Well No. 1
4. Location of Well UNIT LETTER <u>H 6</u> 1980 FEET FROM THE <u>North</u> LINE AND 1980 FEET FROM THE <u>East</u> LINE, SECTION <u>3</u> TOWNSHIP <u>7S</u> RANGE <u>23E</u> NMPM.	10. Field and Pool, or WHdcat <u>Under 1st Pecos Slope ABO</u>
15. Elevation (Show whether DF, RT, GR, etc.) 3805'	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well with 12-1/4" hole on 9-6-82. Drilled with air to 1351' and ran 31 jts 8-5/8", 24#, K-55 casing set at 1351'. Cemented with 700 SX gypseal + 4% CaCl and tailed in with 200 SX "c" + 2% CaCl. PD at 4:00 p.m. 9-8-82. Cement did not circulate, ran temp survey-- TOC at 300'. Set eight plugs with a total of 400 SX "c" + 4% CaCl to circulate cement. Tested BOPS and casing to 600 psi for 30 min - - ok. Reduced hole to 7-7/8" and drilled ahead on 9-10-82. WOC total of 30 hours.

XC: NMOCDA (6), TLS, Cen Reds, ACCTG, Midland, Roswell, ~~REN~~ (file)

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. E. Mathis TITLE Regulatory Coordinator DATE 9-13-82

APPROVED BY Ledie A. Clements TITLE SUPERVISOR, DISTRICT II DATE SEP 17 1982

CONDITIONS OF APPROVAL, IF ANY: