McCLELLAN OIL CORPORATION SANTA FE FEE #11

Section 8-T9S-R25E Chaves County, New Mexico Elevation: 3651' G.L.



LEC 1 1982

W.C.D.

0/17/82: Move in Tex-Mex Rig #3. Spud with 121 bit.

0/18/82: Drilling at 870' with fresh water, 5 min/ft. Prep to run 8-5/8" casing at 900'.

10/19/82: Drilled to 903'. Lost Totco in hole. Fished Totco out with Star Tool. Kan 22 joints of 8-5/8", 24# casing. Cemented with Western, 300 sx Western Lite ½# Flocele, 2% CaCl₂, 250 sx C, 2% CaCl₂. Circulated 75 sx. Cutoff 1:00 a.m. 10-19-82 and resumed drilling. (Set 890' of 8-5/8" casing)

10/20/82: Drilling at 1524'.

10/21/82: Drilling at 2520'.

10/22/82: Drilling at 3265', 1-3 min/ft.

10/23/82: Drilling at 3543'.

10/24/82: Drilling at 3821'.

10/25/82: Drilling at 4100', 5 min/ft. Vis - 41, MW - 9.9, WL - 15.

10/26/82: TD at 4250'. Circulated 4 hours. Vis - 41, MW - 10, WL - 15. Present operation - logging.

10/27/82: Ran Dresser Atlas CNL-FDC and Dual Lateral log. Present operation - running $4\frac{1}{2}$ " casing.

10/28/82: Ran 4217' of $4\frac{1}{2}$ ", $10\frac{1}{2}$ #, J-55 casing. Cemented with 380 sx of Class "C" 50/50 poz with additives. Plug down at 10:00 a.m. 10-27-82. Released rig.