

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
LG 681

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PURPOSES.)

RECEIVED

OIL WELL <input type="checkbox"/>	GAS WELL <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>	7. Unit Agreement Name
Name of Operator Yates Petroleum Corporation ✓			8. Farm or Lease Name Comanche Hill VE State
Address of Operator 207 South 4th St., Artesia, NM 88210			9. Well No. 1
Location of Well UNIT LETTER <u>B</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>36</u> TOWNSHIP <u>10S</u> RANGE <u>25E</u> NMPM.			10. Field and Pool, or WHdcat Wildcat Abo
15. Elevation (Show whether DF, RT, GR, etc.) 3731.2' GR			12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 14-3/4" hole at 5:30 PM 9-22-82. Set 40' of 20" conductor pipe. Ran 24 jts of 10-3/4" 40.5# J-55 casing set at 969'. 1-Texas Pattern notched guide shoe set at 969'. Insert float set at 929'. Cemented w/500 sacks Pacesetter Lite, 3% CaCl. Tailed in w/300 sacks Class "C" w/2% CaCl2. PD 1:30 PM 9-24-82. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 25 sacks. Drilled out 7:30 AM 9-25-82. WOC 18 hours. Nippled up and tested to 1000 psi, okay. Reduced hole to 9-7/8". Drilled plug and resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CHECKED <u>Leslie A. Clements</u>	TITLE <u>Engineering Secretary</u>	DATE <u>9-28-82</u>
Original Signed By Leslie A. Clements Supervisor District II	TITLE <u>SUPERVISOR, DISTRICT II</u>	DATE <u>OCT 1 1982</u>
CONDITIONS OF APPROVAL, IF ANY:		