

UNITED STATES **Artesia, NM 88210**
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: **C-660 FNL & 1980 FNL, Sec. 21, T-5-S**
AT TOP PROD. INTERVAL: **R-25-E**
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) **Spud & set csg.**

5. LEASE

NM 30408

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Rose Federal Cons

9. WELL NO.

12

10. FIELD OR WILDCAT NAME

Pecos Slopes Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 21, S, 25

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3759 Gr

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-28-82: Drilg. 14 3/4" hole to 1002'. Ran 26 jts. 10 3/4" 40.50# csg. set @ 1002'. Cmt w/500 sx Howco Lite #1/4# Flocele, 2% CaCl, followed w/200 sx Class "C" w/2% CaCl. Circ. 150 sx.

12-29-82: Tested Pipe & BOP @ 1000# for 30 mins. Tested O.K.

1-3-83: Drld 7 7/8" hole to TD 4220'. Ran 105 jts. 4 1/2" 10.50# J-55 csg. set @ 4219' w/DV tool @ 2246'. Cmt w/500 sx. 50-50 Pozmix w/3 of 1% CFR-2, .3 of 1% Halid 4 & 5# salt per sx. Plug down @ 11:00 p.m. Open DV tool & circ 4 hrs. Cmt 2nd stage w/1100 sx. 50-50 Pozmix w/5# salt per sx. Plug down @ 4:20 a.m., 1-4-83. Circ. 120 sx. Released rig @ 7:00 a.m., 1-4-83.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *R. L. Dwyer* TITLE **Chief Prod. Clerk** DATE **January 5, 1983**

APPROVED BY
CONDITIONS OF APPROVAL

(ORIG. SGD.) **DAVID R. GLASS**

JAN 17 1983

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

ROSWELL, NEW MEXICO

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1981 O - 347-156

