

NEW MEXICO OIL CONSERVATION COMMISSION
 DRAWER 110
 ARTESIA, NEW MEXICO

RECEIVED
 NOV 2 1982
 O. C. D.
 ARTESIA, OFFICE

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Wallace Oil & Gas</u>		Lease <u>Marshall & Winston</u>			Well # <u>1</u>
Location of Well	Unit <u>D</u>	Section <u>10</u>	Township <u>11S</u>	Range <u>25E</u>	County <u>Chaves</u>
Drilling Contractor	<u>Tex-Mex</u>		Type of Equipment <u>Rotary</u>		

* WITNESS

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>15 1/4"</u>	<u>13 3/8"</u>	<u>48 #</u>	<u>New</u>	<u>450'</u>	<u>circ</u>
* <u>12 1/4"</u>	<u>8 5/8"</u>	<u>24 #</u>	<u>"</u>	<u>1545'</u>	<u>circ</u>
<u>7 7/8"</u>	<u>4 1/2"</u>	<u>10.5 #</u>	<u>"</u>	<u>4150'</u>	<u>3100'</u>

Casing Data:

Surface joints of 13 3/8 inch 48 # Grade J-55

Yes (Approved) (Rejected)

Inspected by B.W. W... date 10-21-82

Cementing Program

Size of hole 15 1/4 Size of Casing 13 3/8 Sacks cement required

Type of Shoe used Tex Pat Float collar used Insert Btm 3 jts welded yes

TD of hole 522 Set 5.15 Feet of 13 3/8 Inch 48 # Grade J-55

New ~~used~~ csg. @ 5.15 with 400 sacks neat cement around shoe

+ 1.50 Thick Wax additives

Plug down @ 11:40 (AM) (~~PM~~) Date 10-21-82

Cement circulated Western No No. of Sacks

Cemented by Western Witnessed by B.W.

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Will one Inch shut