

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <b>Clements Energy Inc</b>		Lease <b>NM 36 A</b>			Well # <b>1</b>
Location of Well	Unit <b>L</b>	Section <b>36</b>	Township <b>14 S</b>	Range <b>26 E</b>	County <b>Chaves</b>
Drilling Contractor	<b>N/A</b>		Type of Equipment <b>ROTARY</b>		

**\* WITNESS** APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<b>17 1/2"</b>	<b>13 3/8"</b>	<b>54.5 #</b>	<b>NEW</b>	<del>370'</del> <b>400'</b>	<b>CIRC</b>
<b>* 12 1/4"</b>	<b>8 5/8"</b>	<b>24 #</b>	<b>"</b>	<b>1500'</b>	<b>CIRC</b>
<b>7 7/8"</b>	<b>4 1/2"</b>	<b>10.5 # &amp; 11.6 #</b>	<b>"</b>	<b>7300'</b>	<b>750</b>

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
(Approved) (Rejected) \_\_\_\_\_

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required \_\_\_\_\_

Type of Shoe used guide Float coliar used insert Btm 3 jts welded yes

TD of hole 1368' Set 1368' Feet of 8 5/8" Inch 24 # Grade J-55

New used csg. @ 1368' with 200 2%cc sacks neat cement around shoe + 405 sax Pacesetter lite additives (1/4# colosal, 2%cc)

Plug down @ 1345 (AM) (PM) Date 3/6/83

Cement circulated yes No. of Sacks 705x

Cemented by Western Co. Witnessed by Mike Stillfield

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: \_\_\_\_\_

