

C/SF

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐ P&A
2. NAME OF OPERATOR
Yates Petroleum Corporation
3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1650 FSL & 330 FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐ ☐
FRACTURE TREAT ☐ ☐
SHOOT OR ACIDIZE ☐ ☐
REPAIR WELL ☐ ☐
PULL OR ALTER CASING ☐ ☐
MULTIPLE COMPLETE ☐ ☐
CHANGE ZONES ☐ ☐
ABANDON* ☒ ☐
(other) ☐ ☐

9. LEASE NM 16091
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME Boaz WO Federal
9. WELL NO. 1
10. FIELD OR WILDCAT NAME Undesignated
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit H, Sec. 10-T5S-R27E
12. COUNTY OR PARISH Chaves 13. STATE NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3957' GR

RECEIVED BY
OCT 05 1983
O. C. D.
ARTESIA, OFFICE

RECEIVED
(NOTE: Report results of multiple completion or zone change on Form 9-330.)
APR 27 1984
OIL & GAS

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations, and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to plug and abandon well as follows:

1. Set CIBP at 4700'.
2. Cut and pull 4½" casing from 4400'.
3. Spot cement plug from CIBP at 4700' up to 50' above 4½" casing stub.
4. Spot cement plug across 8-5/8" casing shoe from 1860'-1760'.
5. Set 25 sacks cement plug at surface.
6. Install regulation abandonment marker.

Verbal approval for the above plugging program given by Mr. George Stewart, Dept. of Interior, Roswell, NM, on 4-25-83.

Surface restoration will be in accordance with landowner-operator agreemtn.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED DAVID R. GLASS TITLE Production Supervisor DATE 4-25-83


APPROVED

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL _____

OCT 4 1983



*See Instructions on Reverse Side