

OIL CONSERVATION DIVISION

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

RECEIVED BY  
OCT 25 1985  
O. C. D.  
ARTESIA OFFICE

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Cibola Energy Corporation ✓	8. Farm or Lease Name CX Plains
3. Address of Operator P. O. Box 1668, Albuquerque, New Mexico 87103	9. Well No. 15
4. Location of Well UNIT LETTER 0 990 FEET FROM THE South LINE AND 1650 FEET FROM THE East LINE, SECTION 19 TOWNSHIP 10S RANGE 28E NMPM.	10. Field and Pool, or Wildcat Race Track San Andre
15. Elevation (Show whether DF, RT, GR, etc.) 3755.2 GR	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIATION WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10/22/85 Spudded well at 4:00 pm with Rotary.

10/23/85 Ran 323' of 8 5/8" casing, texas pattern guide shoe and insert float. Cemented with 227 sx Class C cement with 2% CaCl2. Circulated 90 sx to pit. Bump plug to 750#. Held pressure 30 minutes. WOC 18 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Karon A. [Signature] TITLE Drilling Secretary DATE 10/24/85

APPROVED BY Les A. Clements TITLE Supervisor District 11 DATE OCT 25 1985

CONDITIONS OF APPROVAL, IF ANY: