

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT
NM Oil & Gas Commission
verse side
Drawer DD
Artesia, NM 88210

Expires August 31, 1985

LEASE DESIGNATION AND SERIAL

NM-32322

IF INDIAN, ALLOTTEE OR TRIBE NAME

UNIT AGREEMENT NAME

FARM OR LEASE NAME

Miller Federal

WELL NO.

#2

FIELD AND POOL, OR WILDCAT

W. Pecos Slope Abo

SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

Section 7-6S-23E

COUNTY OR PARISH STATE

Chaves

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED BY

JAN 26 1987

88201 C. D.
ARTEZIA OFFICE

OIL WELL ☐ GAS WELL ☒ OTHER

NAME OF OPERATOR

McKay Oil Corporation

ADDRESS OF OPERATOR

Post Office Box 2014, Roswell, New Mexico 88201 C. D.

LOCATION OF WELL (Report location clearly and in accordance with any State Agency Office
See also space 17 below.)
At surface

1880' FWL & 1980' FNL

PERMIT NO

ELEVATIONS (Show whether DF, RT, GR, etc.)

4214' GR

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Spud & surface csg.

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1-15-87 Drilled 30', 12 1/2", rathole, mousehole.

1-16-87 Ran in hole w/25 jts., 32#, J-55 API casing, set @ 1024', cemented w/150 sxs. Class "C" w/3% CaCl, 150 sxs. Lite "C" w/3% CaCl, plug down @ 2 a.m. Ran TS, survey indicated TOC @ 720'. RIH w/1" Kobe pipe, tagged cement @ 740', brought cement to surface in 10 stages using 350 sxs. Class "C" w/5% CaCl, 670 gals., Aqua Fix, 8 yds. pea gravel.

18. I hereby certify that the foregoing is true and correct

SIGNED Theresa Rodriguez TITLE Production Analyst

DATE 1-19-87

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD
PETER W. CHESTER

JAN 22 1987

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

*See Instructions on Reverse Side