

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-101
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.G.S.	
LAND OFFICE	
OPERATOR	☒

RECEIVED

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No. LG 4927	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT DEPTH. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

JAN 07 '88

1. OIL WELL ☐ GAS WELL ☒ OTHER- ☐		TITE HOLE		O. C. D.	
2. Name of Operator Yates Petroleum Corporation				ARTESIA OFFICE	
3. Address of Operator 105 South 4th St., Artesia, NM 88210				7. Unit Agreement Name Dragonfly State Unit	
4. Location of Well UNIT LETTER <u>D</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>990</u> FEET FROM THE <u>West</u> LINE, SECTION <u>30</u> TOWNSHIP <u>9S</u> RANGE <u>27E</u> NMPM.				8. Farm or Lease Name Dragonfly State Unit	
				9. Well No. 1	
				10. Field and Pool, or WHdcat Wildcat Penn	
15. Elevation (Show whether DF, RT, GR, etc.) 3810.5' GR				12. County Chaves	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data					
NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐		
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐		
PULL OR ALTER CASING ☐		CASING TEST AND CEMENT JOB ☐			
OTHER ☐		OTHER <u>Production Casing, Perforate, Treat</u> ☒			

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 6371'. Reached TD 12-14-87.
12-16-87. Ran 155 joints 5-1/2" 15.5# J-55 casing set 6348'. 1-Regular guide shoe set 6348', float collar set 6309'. Cemented w/300 sx Class "C" with .8% CF-1 and 10% salt (yield 1.32, weight 14.8). PD 5:55 PM 12-16-87. Bumped plug to 1600 psi for 5 minutes, released pressure, float and casing held okay. WOC.
12-22-87. WIH and perforated 5999-6012' (4 SPF-52 holes); 6020-6026' (4 SPF-24 holes), total 76 holes.
12-29-87. Acidized perforations 5999-6026' w/2000 gals 15% NEFE acid and 125 ball sealers.

TITE HOLE!

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mike Williams TITLE Production Supervisor DATE 1-5-88

Original Signed By
Mike Williams

APPROVED BY Oil & Gas Inspector TITLE DATE JAN 12 1988

CONDITIONS OF APPROVAL, IF ANY: