STATE OF NEW MEXICO ENERGY AND IMPERALS DEPARTMENT

SANTA FE. NEW MEXICO 87 SECENCE		SION	
SANTA FE. NEW MEXICO BY RECEIVED File Fi		31011	Farm C-103
SUNDRY NOTICES AND REPORTS ON WELLS OF REAL OF THE PROPOSED OF THE TIME OF THE CASHE PLANS OF THE PROPOSED OF THE PLANS OF		RECEIVINA	Reitsed 10-1-
SUNDRY NOTICES AND REPORTS ON WELLS OC. L. OC. MOTIVELY THIS FORM FOR REGISTRATE AND REPORTS ON WELLS OC. L. OC. MOTIVELY THIS FORM FOR REGISTRATE AND REPORTS ON WELLS OC. L. OC. MOTIVELY THIS FORM FOR REGISTRATE AND REPORTS ON WELLS OC. L. OC. L. OC. MOTIVELY THIS FORM FOR REGISTRATE AND REPORTS ON WELLS OC. L. O	TILE IN SANTA PE, NEW MEXICO 8/3		<u> </u>
SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS O. C. U SUNDRY NOTICES AND REPORTS ON WELLS O. C. U SUNDRY NOTICES AND REPORTS ON WELLS O. C. U SUNDRY NOTICES AND REPORTS ON WELLS O. C. U SUNDRY NOTICES AND REPORTS ON WELLS O. C. U SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICE OF INTENTION TO: Sundress of Operation	}	l (→ ``	LJ
SUNDRY NOTICES AND REPORTS ON WELLS O. C. L ONLY CONTROL OF THE PROPERTY NOTICES AND REPORTS ON WELLS O. C. L ONLY CONTROL OF THE CONTROL	LAND OFFICE		
SUNDRY NOTICES AND REPORTS ON WELLS O. C. D. OTHER SUNDRY OF ICES AND REPORTS ON WELLS OTHER TO SOUTH A PROPERTY OF THE P	DERATOA		
The second structure of Notice of No			
The state of the s	SUNDRY NOTICES AND REPORTS ON WELLS		
Desert Rose Unit Norms of Operator Yates Petroleum Corporation Address of Operator 105 South 4th St., Artesia, NM 88210 Location of Well UNIT LETTER P. 660 FEET FROM THE SOUth LINE AND 660 FEET FROM 18. Furn or Lesse Home Desert Rose Unit 9. Well NO. 2 10. Field and Pool, or Wildcat South Pecos Slope At THE East LINE, SECTION 11 TOWNSHIP 9S RANGE 26E NUMBER. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: ACTEGINA SUBSEQUENT REPORT OF: CAPAGEM RELIGIAL WORK CONFILING OPPRIS. CASING TEST AND COMMENT JOS. Spudded 26" hole with Frank's rathole 2:15 PM 12-2-87. Set 40' of 20" conductor pipe. Resumed drilling 12-1/4" hole with rotary 6:00 PM 12-3-87. Ran 23 joints 8-5/8" 24# J-55 casing set 950'. I-Texas Pattern Notched guide shoe set 950', insert float set 908'. Cemented w/375 sx Lite + 1/4#/sx Cellsoeal + 5#/sx Gilsonite and 3% Cacl2 (yield 1.8, weight 12.8). Tailed in w/200 sx Class "C" with 2% Cacl2 (yield 1.3, weight 14.8). PD 5:00 PM 12-4-87. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sx. WOC. Drilled out 6:00 AM 12-5-87. WOC	(DO NOT USE THIS PORM FOR PROPOSALS TO PAILL OF TO DECPEN OF PLUG BACK TO A DIFFERENCE OF THE COURT OF THE CO	MESIA, OFFICE	
Nome of Operator Yates Petroleum Corporation Address of Operator 105 South 4th St., Artesia, NM 88210 Location of Well UNIT CETTER P 660 Check Appropriate Box To Indicate Nature of Notice, Report of Other Data NOTICE OF INTENTION TO: CHAPCE PLANS CHAPTE PLUE AND ABANDON CHAPTE STATE AND CEMENT JUB SUBSEQUENT REPORT OF: CHAPCE PLANS CHAPTE PLUE AND ABANDON CHAPTE STATE AND CEMENT JUB STATE AND CEMENT JUB STATE AND CEMENT JUB STATE AND ABANDON CHAPTE STATE AND CEMENT JUB STATE AND CEMENT JUB STATE AND CEMENT JUB STATE AND ABANDON CHAPTE STATE AND CEMENT JUB STATE AND CEMENT JUB STATE AND ABANDON CHAPTE STATE AND ABANDON CHAPTER STATE	AU ()	7. Unit Agreement	Name
Pates Petroleum Corporation Address of Operator 105 South 4th St., Artesia, NM 88210 Location of Well UNIT LETTER P . 660 TEXT FROM THE SOUTH LINE AND 660 THE East Line Section 11 Township 9S RANGE 26E MAPPIN. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: ALTERNAC PLANS CHANGE PLAN	WELL WELL WELL WE OTHER-		
Address of Coern.or 105 South 4th St., Artesia, NM 88210 2 Location of Well Unit letter P 660 TEST FROM THE SOUTH LINE AND 660 THE East LINE, SECTION 11 TOWNSHIP 9S RAMEE 26E NUMBER. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: STOOM REMEDIAL WORK CHANGE PLANS CHANGE PLANS SPUGAND ABANDON CHANGE PLANS CHANGE PLANS SPUGAND ABANDON CHANGE TEST AND CEMENT JOB SPUGAND ABANDON CHANGE TOWN THE TOWN THE TOWN THE TOWN TOWN TOWN TOWN TOWN TOWN TOWN TOWN		8. Farm or Lease	liame
Location of Well UNIT LETTER P 660 THE East LINE, SECTION 11 TOWNSHIP 9S RANGE 26E Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: CHANGE PLANS CASING CHANGE PLANS CASING CASING TEST AND CEMENT JOB XX OTHER OTHER CDESCRIBE PROPOSED OF COMMERCE 103. Spudded 26" hole with Frank's rathole 2:15 PM 12-2-87. Set 40' of 20" conductor pipe. Resumed drilling 12-1/4" hole with rotary 6:00 PM 12-3-87. Ran 23 joints 8-5/8" 24# J-55 casing set 950'. 1-Texas Pattern Notched guide shoe set 950', insert float set 908'. Cemented W/375 sx Lite + 1/4#/sx Cellsoeal + 5#/sx Gilsonite and 3% Cacl2 (yield 1.8, weight 12.8). Tailed in w/200 sx Class "C" with 2% Cacl2 (yield 1.3, weight 14.8). PD 5:00 PM 12-4-87. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sx. WOC. Drilled out 6:00 AM 12-5-87. WOC	Yates Petroleum Corporation \bigvee	Desert Ros	e Unit
Location of Well UNIT LETTER P 660 FEET FROM THE SOUTH LINE AND 660 FEET FROM SOUTH PECOS Slope At THE East LINE, SECTION 11 TOWNSHIP 9S RANGE 26E MAPPIN. 15. Elevation (Show whether DF, RT, GR, etc.) 3802' GR Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: CHANGE PLANS CHANGE OF ILLINE OF PLUG AND ABANDON CHANGE PLANS CASING FEET AND CEMENT JOB X OTHER OTHER Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Width Frank's rathole 2:15 PM 12-2-87. Set 40' of 20" conductor pipe. Resumed drilling 12-1/4" hole with rotary 6:00 PM 12-3-87. Ran 23 joints 8-5/8" 24# J-55 casing set 950'. 1-Texas Pattern Notched guide shoe set 950', insert float set 908'. Cemented w/375 sx Lite + 1/4#/sx Cellsoeal + 5#/sx Gilsonite and 3% CaCl2 (yield 1.8, weight 12.8). Tailed in w/200 sx Class "C" with 2% CaCl2 (yield 1.3, weight 14.8). PD 5:00 PM 12-4-87. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sx. WOC. Drilled out 6:00 AM 12-5-87. WOC	•	9, Well No.	
South Pecos Slope At the East Line, section 11 Township 9S RANGE 26E NAME. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: ACMEDIAL WORK COMMENCE OBJILLING OPHS. CHANGE PLANS OTHER OTHER OTHER Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed William 12-1/4" hole with rotary 6:00 PM 12-3-87. Set 40' of 20" conductor pipe. Resumed drilling 12-1/4" hole with rotary 6:00 PM 12-3-87. Ran 23 joints 8-5/8" 24# J-55 casing set 950'. 1-Texas Pattern Notched guide shoe set 950', insert float set 908'. Cemented W/375 sx Lite + 1/4#/sx Cellsoeal + 5#/sx Gilsonite and 3% CaCl2 (yield 1.8, weight 12.8). Tailed in w/200 sx Class "C" with 2% CaCl2 (yield 1.3, weight 14.8). PD 5:00 PM 12-4-87. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sx. WOC. Drilled out 6:00 AM 12-5-87. WOC	105 South 4th St., Artesia, NM 88210	2	
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: CHANGE PLANS CHANGE PLANS SPUNDENCE ORDICAL WORK CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS SPUNDENCE ORDICAL WORK CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS SPUNDENCE ORDICAL WORK CHANGE PLANS COMMENCE ORDICLING OPNS. CASING TEST AND CEMENT JOB OTHER OTHER COMMENCE ORDICING OPNS. CASING TEST AND CEMENT JOB OTHER OTHER COMMENCE ORDICING OPNS. CASING TEST AND CEMENT JOB OTHER OTHER COMMENCE ORDICING OPNS. CASING TEST AND CEMENT JOB OTHER OTHER COMMENCE ORDICING OPNS. CASING TEST AND CEMENT JOB OTHER OTHER COMMENCE ORDICING OPNS. CASING TEST AND CEMENT JOB OTHER COMMENCE ORDICING OPNS. CASING TEST AND CEMENT JOB COMMENCE ORDICING OPNS. CASING TEST AND CEMENT JOB OTHER COMMENCE ORDICING OPNS. CASING TEST AND CEMENT JOB COMMENCE ORDICING OPNS. CASING TEST AND CEMENT JOB COMMENCE ORDICING	Location of Well .	10. Field and Poo	l, or Wildcat
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: CHANGE PLANS CHANGE PLANS SPUNDENCE ORDICAL WORK CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS SPUNDENCE ORDICAL WORK CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS SPUNDENCE ORDICAL WORK CHANGE PLANS COMMENCE ORDICLING OPNS. CASING TEST AND CEMENT JOB OTHER OTHER COMMENCE ORDICING OPNS. CASING TEST AND CEMENT JOB OTHER OTHER COMMENCE ORDICING OPNS. CASING TEST AND CEMENT JOB OTHER OTHER COMMENCE ORDICING OPNS. CASING TEST AND CEMENT JOB OTHER OTHER COMMENCE ORDICING OPNS. CASING TEST AND CEMENT JOB OTHER OTHER COMMENCE ORDICING OPNS. CASING TEST AND CEMENT JOB OTHER COMMENCE ORDICING OPNS. CASING TEST AND CEMENT JOB COMMENCE ORDICING OPNS. CASING TEST AND CEMENT JOB OTHER COMMENCE ORDICING OPNS. CASING TEST AND CEMENT JOB COMMENCE ORDICING OPNS. CASING TEST AND CEMENT JOB COMMENCE ORDICING	P 660 South 6	60 South Pecos	Slope Abo
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: REMEDIAL WORK MPORABLY ABARDON CLOS ALTER CASING CHANGE PLANS ALTERING CASING CHANGE PLANS CASING TEST AND CEMENT JUB STANDORM ALTERING CASING CHANGE PLANS CASING TEST AND CEMENT JUB STANDORM CHANGE PLANS CASING TEST AND CEMENT JUB STANDORM CHANGE PLANS CASING TEST AND CEMENT JUB STANDORM CA	VALUE CELLER LINE AND PEET FROM THE LINE AND V	1111111	mmm
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: REMEDIAL WORK MPPRABILY ABANDON CHANGE PLANS OTHER OTHER Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any properties in part of the plans of	East 11 99	26F (
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: ALTERING CASING PLUG AND ABANDON CHANGE PLANS CASING TEST AND CEMENT JOB OTHER Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed drilling 12-1/4" hole with rotary 6:00 PM 12-2-87. Set 40' of 20" conductor pipe. Resumed drilling 12-1/4" hole with rotary 6:00 PM 12-3-87. Ran 23 joints 8-5/8" 24# J-55 casing set 950'. 1-Texas Pattern Notched guide shoe set 950', insert float set 908'. Cemented w/375 sx Lite + 1/4#/sx Cellsoeal + 5#/sx Gilsonite and 3% CaCl2 (yield 1.8, weight 12.8). Tailed in w/200 sx Class "C" with 2% CaCl2 (yield 1.3, weight 14.8). PD 5:00 PM 12-4-87. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sx. WOC. Drilled out 6:00 AM 12-5-87. WOC	THE LINE, SECTION TOWNSHIP PANGE		
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: ALTERING CASING PLUG AND ABANDON CHANGE PLANS CASING TEST AND CEMENT JOB OTHER Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Resumed drilling 12-1/4" hole with rotary 6:00 PM 12-2-87. Set 40' of 20" conductor pipe. Resumed drilling 12-1/4" hole with rotary 6:00 PM 12-3-87. Ran 23 joints 8-5/8" 24# J-55 casing set 950'. 1-Texas Pattern Notched guide shoe set 950', insert float set 908'. Cemented w/375 sx Lite + 1/4#/sx Cellsoeal + 5#/sx Gilsonite and 3% CaCl2 (yield 1.8, weight 12.8). Tailed in w/200 sx Class "C" with 2% CaCl2 (yield 1.3, weight 14.8). PD 5:00 PM 12-4-87. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sx. WOC. Drilled out 6:00 AM 12-5-87. WOC	15. Elevation (Show whether DF, RT, GR, etc.)	12. County	44444
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: ALTERING CASING CHANGE PLANS CHANGE PLANS CHANGE PLANS CASING TEST AND CEMENT JQB CASING TEST AND CEMENT JQB CASING TEST AND CEMENT JQB OTHER Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any property took) SEE RULE 1703. Spudded 26" hole with Frank's rathole 2:15 PM 12-2-87. Set 40' of 20" conductor pipe. Resumed drilling 12-1/4" hole with rotary 6:00 PM 12-3-87. Ran 23 joints 8-5/8" 24# J-55 casing set 950'. 1-Texas Pattern Notched guide shoe set 950', insert float set 908'. Cemented w/375 sx Lite + 1/4#/sx Cellsoeal + 5#/sx Gilsonite and 3% CaCl2 (yield 1.8, weight 12.8). Tailed in w/200 sx Class "C" with 2% CaCl2 (yield 1.3, weight 14.8). PD 5:00 PM 12-4-87. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sx. WOC. Drilled out 6:00 AM 12-5-87. WOC		1	IIIIIII
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: SUBSEQUENT SU			-1111111111
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed date of starting any proposed date of starting any proposed or Completed date of starting any proposed date of starting any prop		}-==	
Spudded 26" hole with Frank's rathole 2:15 PM 12-2-87. Set 40' of 20" conductor pipe. Resumed drilling 12-1/4" hole with rotary 6:00 PM 12-3-87. Ran 23 joints 8-5/8" 24# J-55 casing set 950'. 1-Texas Pattern Notched guide shoe set 950', insert float set 908'. Cemented w/375 sx Lite + 1/4#/sx Cellsoeal + 5#/sx Gilsonite and 3% CaCl2 (yield 1.8, weight 12.8). Tailed in w/200 sx Class "C" with 2% CaCl2 (yield 1.3, weight 14.8). PD 5:00 PM 12-4-87. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sx. WOC. Drilled out 6:00 AM 12-5-87. WOC	_		i
Spudded 26" hole with Frank's rathole 2:15 PM 12-2-87. Set 40' of 20" conductor pipe. Resumed drilling 12-1/4" hole with rotary 6:00 PM 12-3-87. Ran 23 joints 8-5/8" 24# J-55 casing set 950'. 1-Texas Pattern Notched guide shoe set 950', insert float set 908'. Cemented w/375 sx Lite + 1/4#/sx Cellsoeal + 5#/sx Gilsonite and 3% CaCl2 (yield 1.8, weight 12.8). Tailed in w/200 sx Class "C" with 2% CaCl2 (yield 1.3, weight 14.8). PD 5:00 PM 12-4-87. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sx. WOC. Drilled out 6:00 AM 12-5-87. WOC	OTHER		
Resumed drilling 12-1/4" hole with rotary 6:00 PM 12-3-87. Ran 23 joints 8-5/8" 24# J-55 casing set 950'. 1-Texas Pattern Notched guide shoe set 950', insert float set 908'. Cemented w/375 sx Lite + 1/4#/sx Cellsoeal + 5#/sx Gilsonite and 3% CaCl2 (yield 1.8, weight 12.8). Tailed in w/200 sx Class "C" with 2% CaCl2 (yield 1.3, weight 14.8). PD 5:00 PM 12-4-87. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sx. WOC. Drilled out 6:00 AM 12-5-87. WOC	OTHEROTHER		tarting any propose
13 hrs. NU and tested to 1000 psi for 30 mins, OK. Reduced hole to $7-7/8$ ". Drilled plug and resumed drilling.	OTHEROTHER	nent dates, including estimated date of s	

s /		ete to the best of my knowledge and belief.	
a sento Cont	- Jothell	Production Supervisor	DATE 12-8-87
APPROVED BY	Original Si gned I Mike Williams	By	DEC 3 1 1987
	Oil & Gas Inches		