

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator Yates Petr. Corp		Lease EaKin AFB Com		Well # 1	
Location of Well	Unit C	Section 17	Township 10	Range 25	County Eddy
Drilling Contractor	Undes.		Type of Equipment Rotary		
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
12 1/4	8 5/8	24# J-55		1300	900 Circ
7 7/8	4 1/2	9.5# J-55		TD	400
Casing Data:					
Surface _____ joints of _____ inch _____ # Grade _____					
(Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required _____					
Type of Shoe used guide Float collar used insert Btm 3 jts welded yes					
TD of hole 862' Set 862' Feet of 8 5/8" Inch 24 # Grade J-55					
New-used csg. @ 862' with 150 270cc sacks neat cement around shoe					
+ 300 sax Pacemaker lite additives (1/4" celoseal, 370 gal., 370 cc)					
Plug down @ 10830 (AM) (PM) Date 4-28-88					
Cement circulate No No. of Sacks -0-					
Cemented by Western Co. Witnessed by Mike Stillfield					
Temp. Survey ran @ 4830 (AM) (PM) Date 4-28-88 top cement @ 250'					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks:					
1. Ran 1 Tubing + Tagged to 128' w/ 100 sx cement.					
2. Ran 1" Tubing + Tagged to 40' w/ 40 sx cement.					
cement circulated to surface.					