

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Artesia, NM 88210

Form approved,
Budget Bureau No. 1004-6135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM-14983

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Monaghan QY Federal

9. WELL NO.

12

10. FIELD AND POOL OR WILDCAT

Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit 0, Sec. 28-T5S-R24E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different depth. Use "APPLICATION FOR PERMIT--" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

105 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

660' FML & 1980' FEL

14. PERMIT NO.

API #30-005-62621

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4067.2' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud & set surface casing

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 26" hole at 10:50 AM 5-24-88 with Frank's Rathole. Set 40' of 20" conductor pipe. Notified Stan Mayo, BLM, Roswell, NM, of spud. Resumed drilling 12-1/4" hole 9:00 AM 5-28-88. Ran 28 joints 9-5/8" 36# J-55 ST&C casing set 1200'. Texas pattern notched guide shoe set 1200', insert float set 1157'. Cemented w/700 sx Pacesetter Lite with 1/2# Celloseal, 10# Gilsonite and 3% CaCl2 (yield 2.16, weight 12.1). Tailed in w/150 sx Class C with 2% CaCl2 (yield. 1.32, weight 14.8). PD 1:30 PM 5-30-88. Bumped plug to 650 psi, released pressure and float held okay. Cement circulated 35 sacks. WOC. WOC 18 hrs and 45 minutes. Drilled out 8:15 AM 5-31-88. NU and tested to 1000 psi for 15 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production Supervisor

DATE 6-1-88

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

RECEIVED
MAY 31 9 00 AM '88
BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

ACCEPTED FOR RECORD
PATRICK W. CHESTER

JUN 15 1988

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA