

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Artesia, NM 88210

NM Oil Cons. Commission
(Other Instructions on Reverse Side)

Form approved.
Budget Bureau No. 1004-013
Expires August 31, 1985

25F

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR
Yates Petroleum Corporation

3. ADDRESS OF OPERATOR
105 South 4th st., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

14. PERMIT NO.
API #30-005-62621

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
4067.2' GR

660' FNL & 1980' FEL

JUN 21 '88
O. C. D.
ARTESIA, OFFICE

5. LEASE DESIGNATION AND SERIAL NO.
NM-14983

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Monaghan QY Federal

9. WELL NO.
12

10. FIELD AND POOL OR WILDCAT
Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit 0, Sec. 28-T5S-R24E

12. COUNTY OR PARISH
Chaves

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD 4250'. Reached TD 4:00 PM 6-4-88. Ran 102 jts 4-1/2" 9.5# J-55 ST&C casing, set 4250'. Regular guide shoe set 4250', float collar 402'. Cemented w/500 sx 65/35 Poz "C" with .7% CF-1, 5# salt, 1/4# Celloseal (yield 1.39, weight 14.2). PD 10:15 PM 6-5-88. Bumped plug to 1700 psi for 2 minutes, released pressure and float held okay. WOC.

Perforated 11 .42" holes as follows: 3664, 66, 68, 69, 70 and 72' (6 holes); 4018, 20, 22, 24 and 4026' (5 holes). Acidized perforations in two stages w/2500 gals 7 1/2% NEFE acid and N₂. Frac'd perforations 3664-4026' (via 4-1/2" casing) w/30000 gals gelled KCL water and 53000# 20/40 sand.

RECEIVED
JUN 15 11 00 AM '88
CARTER AREA

18. I hereby certify that the foregoing is true and correct

SIGNED *Quanta D. Collins*

TITLE Production Supervisor

DATE 6-14-88

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
DATE PETER W. CHESTER

JUN 17 1988

BUREAU OF LAND MANAGEMENT
JOSWELL RESOURCE AREA

*See Instructions on Reverse Side